

89450242 Information

Heisener.com

Part Number 89450242 **Manufacturer** Crouzet

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 24V 240W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









89450242 Specifications

Manufacturer Part Number 89450242 Manufacturer Crouzet Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Manufacturer Part Number	89450242
Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Manufacturer	Crouzet
Package - Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series Millenium Supply, 89450 Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)		AC DC Converters
Type Linear Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Package	-
Number of Outputs 1 Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Series	Millenium Supply, 89450
Voltage - Input 230VAC Voltage - Output 1 24V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Туре	Linear
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Site / Dimension 240V Current - Output (Max) - Current - Output (Max) 10A - Current - Output (Max) 240W Applications ITE (Commercial) 3kV (3000V) Chassis Mount Teatures Universal Input Chassis Mount 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 60°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Coutput 4 - Current - Output (Max) 10A Power (Watts) 240W Applications ITE (Commercial) 3kV (3000V) Commercial 10C	Voltage - Input	230VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation Sifficiency Operating Temperature O°C ~ 60°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension - Current - Output (Max) 10A - Current - Output (Max) 10A - Commercial) 3kV (3000V) Chassis Mount 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Voltage - Output 1	24V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature O°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension - Comparing Temperature 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 10A 240W OV Commercial) AkV (3000V) Commercial) Commercial) AkV (3000V) Commercial) Commercial) Commercial) AkV (3000V) Commercial) Commercial Commercial) Commercial Commercial	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Current - Output (Max)	10A
Voltage - Isolation 3kV (3000V) Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Power (Watts)	240W
Efficiency - Operating Temperature 0°C ~ 60°C (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating) Features Universal Input Mounting Type Chassis Mount Size / Dimension $7.87^{\circ}\text{L x } 3.86^{\circ}\text{W x } 2.56^{\circ}\text{H } (200.0\text{mm x } 98.0\text{mm x } 65.0\text{mm})$	Voltage - Isolation	3kV (3000V)
Features Universal Input Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Efficiency	-
Mounting Type Chassis Mount Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Operating Temperature	$0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ (With Derating)
Size / Dimension 7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	7.87" L x 3.86" W x 2.56" H (200.0mm x 98.0mm x 65.0mm)
		Report errors?

89450242 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

89450242 Payment Methods





















89450242 Shipping Methods













If you have any question about 89450242, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com