

### **8951410010 Information**

Heisener.com

Part Number 8951410010 Manufacturer Weidmuller

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 24V 500W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 8951410010 Specifications

Manufacturer Part Number         8951410010           Manufacturer         Weidmuller           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         PRO-M           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)			
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         PRO-M           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Manufacturer Part Number	8951410010	
Package         -           Series         PRO-M           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Manufacturer	Weidmuller	
Package         -           Series         PRO-M           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         PRO-M           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)		AC DC Converters	
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Package	-	
Number of Outputs       1         Voltage - Input       85 ~ 264 VAC         Voltage - Output 1       24V         Voltage - Output 2       -         Voltage - Output 3       -         Voltage - Output 4       -         Current - Output (Max)       20A         Power (Watts)       500W         Applications       ITE (Commercial)         Voltage - Isolation       4kV (4000V)         Efficiency       90%         Operating Temperature       -25°C ~ 70°C (With Derating)         Features       Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input         Mounting Type       DIN Rail         Size / Dimension       5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Series	PRO-M	
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         20A           Power (Watts)         500W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         90%           Operating Temperature         -25°C ~ 70°C (With Derating)           Features         Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input           Mounting Type         DIN Rail           Size / Dimension         5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Type	Enclosed	
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -25°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type  Size / Dimension  24V  24V  24V  24V  24V  26V  26V  26V	Number of Outputs	1	
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -25°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Voltage - Input	85 ~ 264 VAC	
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  90%  Operating Temperature  -25°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Voltage - Output 1	24V	
Voltage - Output 4  Current - Output (Max)  20A  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  90%  Operating Temperature  -25°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Voltage - Output 2	-	
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  90%  Operating Temperature  -25°C ~ 70°C (With Derating)  Features  Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Voltage - Output 3	-	
Power (Watts) 500W  Applications ITE (Commercial)  Voltage - Isolation 4kV (4000V)  Efficiency 90%  Operating Temperature -25°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Voltage - Output 4	-	
Applications ITE (Commercial)  Voltage - Isolation 4kV (4000V)  Efficiency 90%  Operating Temperature -25°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Current - Output (Max)	20A	
Voltage - Isolation 4kV (4000V)  Efficiency 90%  Operating Temperature -25°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Power (Watts)	500W	
Efficiency 90%  Operating Temperature -25°C ~ 70°C (With Derating)  Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Applications	ITE (Commercial)	
Operating Temperature  -25°C ~ 70°C (With Derating)  Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type  DIN Rail  Size / Dimension  5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Voltage - Isolation	4kV (4000V)	
Features Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input  Mounting Type DIN Rail  Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Efficiency	90%	
Mounting Type DIN Rail Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Operating Temperature	-25°C ~ 70°C (With Derating)	
Size / Dimension 5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	Features	Adjustable Output, DC Input Capable, IP20, Load Sharing, Universal Input	
	Mounting Type	DIN Rail	
Report errors?	Size / Dimension	5.91" L x 4.76" W x 5.12" H (150.0mm x 121.0mm x 130.0mm)	
			Report errors?

#### 8951410010 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 8951410010 Payment Methods

































If you have any question about 8951410010, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com