

8957040000 Information



For Reference Only

Part Number 8957040000 Manufacturer Weidmuller Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 12A 48V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8957040000 Specifications

| Manufacturer 8957040000 Manufacturer Weidmuller Category Relays Power Relays, Over 2 Amps Package - Series RCM Relay Type General Purpose Coil Type Non Latching Coil Current 15.6mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 40VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | | |
|---|--------------------------|---|
| CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm) | Manufacturer Part Number | 8957040000 |
| Package - Series RCM Relay Type General Purpose Coil Type Non Latching Coil Current 15.6mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Manufacturer | Weidmuller |
| Package-SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm) | Category | Relays |
| SeriesRCMRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm) | | Power Relays, Over 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current15.6mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)12ASwitching Voltage400VAC - MaxTurn On Voltage (Max)36 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time10msFeaturesDiode, LED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.110" (2.8mm) | Package | - |
| Coil Type Non Latching Coil Current 15.6mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Series | RCM |
| Coil Current Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Relay Type | General Purpose |
| Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Coil Type | Non Latching |
| Contact Form DPDT (2 Form C) Contact Rating (Current) 12A Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Coil Current | 15.6mA |
| Contact Rating (Current) Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Coil Voltage | 48VDC |
| Switching Voltage 400VAC - Max Turn On Voltage (Max) 36 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Contact Form | DPDT (2 Form C) |
| Turn On Voltage (Max) Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Contact Rating (Current) | 12A |
| Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Switching Voltage | 400VAC - Max |
| Operate Time 15ms Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Turn On Voltage (Max) | 36 VDC |
| Release Time 10ms Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Turn Off Voltage (Min) | 4.8 VDC |
| Features Diode, LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Operate Time | 15ms |
| Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Release Time | 10ms |
| Termination Style Plug In, Quick Connect - 0.110" (2.8mm) | Features | Diode, LED Indicator, Test Button |
| | Mounting Type | Socketable |
| Report errors? | Termination Style | Plug In, Quick Connect - 0.110" (2.8mm) |
| * | | Report errors? |

8957040000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8957040000 Payment Methods





















8957040000 Shipping Methods













If you have any question about 8957040000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com