

89847-330LF Information

Heisener.com

For Reference Only

Part Number 89847-330LF **Manufacturer** Amphenol FCI

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT 60POS .100" DBL PCB

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









89847-330LF Specifications

Manufacturer Part Number Manufacturer Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions Mumber of Positions Loaded Pitch - Mating O.100" (2.54mm) Number of Rows Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Contact Finish - Mating Contact Finish - Mating O.30jin (0.76µm) Insulation Color Blue Insulation Height Contact Length - Post O.102" (2.56mm) Contact Length - Post O.102" (2.60mm) Contact Length - Post O.102" (2.60mm) Contact Length - Post O.102" (2.60mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Blue Insulation Height Contact Length - Post 0.102" (2.60mm)	Manufacturer Part Number	89847-330LF
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Manufacturer	Amphenol FCI
Package - Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Category	Connectors, Interconnects
Series Dubox? Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Female Socket Style Board to Board Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Series	Dubox?
Style Board to Board Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Connector Type	Receptacle
Number of Positions60Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Number of Positions	60
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.102" (2.60mm)	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Insulation Height Contact Length - Post Gold 30µin (0.76µm) Blue 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Termination	Solder
Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Fastening Type	Push-Pull
Insulation Color Insulation Height O.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Contact Finish - Mating	Gold
Insulation Height 0.335" (8.51mm) Contact Length - Post 0.102" (2.60mm)	Contact Finish Thickness - Mating	30μin (0.76μm)
Contact Length - Post 0.102" (2.60mm)	Insulation Color	Blue
	Insulation Height	0.335" (8.51mm)
Operating Temperature -	Contact Length - Post	0.102" (2.60mm)
T ···· O · T ·····	Operating Temperature	-
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

89847-330LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

89847-330LF Payment Methods



















89847-330LF Shipping Methods













If you have any question about 89847-330LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com