

89885-302LF Information

Heisener.com

For Reference Only

Part Number 89885-302LF **Manufacturer** Amphenol FCI

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT 2POS .100" DUAL ENTRY

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









89885-302LF Specifications

Manufacturer Part Number 89885-302LF Manufacturer Amphenol FCI Category Connectors, Interconnects Package - Scries Dubox? Connector Type Receptacle, Bottom or Top Entry Contact Type Female Socket Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Testening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature - Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series Dubox? Connector Type Receptacle, Bottom or Top Entry Contact Type Female Socket Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Manufacturer Part Number	89885-302LF
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Dubox? Connector Type Receptacle, Bottom or Top Entry Contact Type Female Socket Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Blue Insulation Height Contact Length - Post Operating Temperature - Receptacles, Female Socket Dubox? Leaders, Receptacles, Female Sockets Dubox? Leaders, Receptacles, Female Sockets Dubox? Leaders Socket Dubox? Leaders Socket Dubox? Leaders Socket Dubox Pemale Socket Dubox	Manufacturer	Amphenol FCI
Package-SeriesDubox?Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Category	Connectors, Interconnects
SeriesDubox?Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Series	Dubox?
StyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Connector Type	Receptacle, Bottom or Top Entry
Number of Positions 2 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Style	Board to Board
Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Number of Positions	2
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post Operating Temperature -	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.104" (2.65mm)Operating Temperature-	Termination	Solder
Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Blue Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Fastening Type	Push-Pull
Insulation Color Insulation Height Contact Length - Post Operating Temperature Blue 0.335" (8.51mm) 0.104" (2.65mm)	Contact Finish - Mating	Gold
Insulation Height 0.335" (8.51mm) Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Contact Finish Thickness - Mating	30μin (0.76μm)
Contact Length - Post 0.104" (2.65mm) Operating Temperature -	Insulation Color	Blue
Operating Temperature -	Insulation Height	0.335" (8.51mm)
	Contact Length - Post	0.104" (2.65mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

89885-302LF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

89885-302LF Payment Methods



















89885-302LF Shipping Methods













If you have any question about 89885-302LF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com