

8A2061-Z Information



For Reference Only

Part Number 8A2061-Z

Manufacturer Copal Electronics Inc.

Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8A2061-Z Specifications

Manufacturer Part Number 8A2061-Z Manufacturer Copal Electronics Inc. Category Switches Package - Series 8A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection		
Category Switches Package - Series 8A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Manufacturer Part Number	8A2061-Z
Package - Series 8A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Manufacturer	Copal Electronics Inc.
Package - Series 8A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Category	Switches
Series 8A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection		Toggle Switches
Circuit DPDT Switch Function On-Mom Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125 V Voltage Rating - DC 30 V Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Package	-
Switch FunctionOn-MomCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Series	8A
Current Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Switch Function	On-Mom
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Current Rating	6A (AC), 4A (DC)
Actuator Type Standard Round Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Voltage Rating - AC	125V
Actuator Length 10.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Voltage Rating - DC	30V
Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Actuator Length	10.50mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesSealed - Flux Protection	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Sealed - Flux Protection	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia 1/4-40 Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Sealed - Flux Protection	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection Features Sealed - Flux Protection	Termination Style	Solder Lug
Ingress Protection - Sealed - Flux Protection	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Sealed - Flux Protection	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Sealed - Flux Protection
		Report errors?

8A2061-Z Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8A2061-Z Payment Methods





















8A2061-Z Shipping Methods













If you have any question about 8A2061-Z, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com