

8ETL06 Information



For Reference Only

Part Number 8ETL06

Manufacturer Vishay Semiconductor Diodes Division

Category Discrete Semiconductor Products

Diodes - Rectifiers - Single

Description DIODE GEN PURP 600V 8A TO220AC

Package TO-220-2

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8ETL06 Specifications

Manufacturer Part Number8ETL06ManufacturerVishay Semiconductor Diodes DivisionCategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-220-2SeriesFRED Pt?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.05 V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	oz i z o spremenions	
CategoryDiscrete Semiconductor ProductsDiodes - Rectifiers - SinglePackageTO-220-2SeriesFRED Pt?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.05V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5µA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	Manufacturer Part Number	8ETL06
PackageDiodes - Rectifiers - SinglePackageTO-220-2SeriesFRED Pt?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.05V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	Manufacturer	Vishay Semiconductor Diodes Division
PackageTO-220-2SeriesFRED Pt?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.05 V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	Category	Discrete Semiconductor Products
SeriesFRED Pt?Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.05V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C		Diodes - Rectifiers - Single
Diode TypeStandardVoltage - DC Reverse (Vr) (Max)600VCurrent - Average Rectified (Io)8AVoltage - Forward (Vf) (Max) @ If1.05V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	Package	TO-220-2
Voltage - DC Reverse (Vr) (Max) Current - Average Rectified (Io) 8A Voltage - Forward (Vf) (Max) @ If 1.05V @ 8A Speed Fast Recovery = < 500ns, > 200mA (Io) Reverse Recovery Time (trr) 250ns Current - Reverse Leakage @ Vr 5μA @ 600V Capacitance @ Vr, F Mounting Type Through Hole Package / Case TO-220-2 Supplier Device Package Operating Temperature - Junction 600V 1.05V @ 8A Fast Recovery = < 500ns, > 200mA (Io) 250ns Through Hole - Capacitance @ Vr, F Through Hole To-220-2 Supplier Device Package TO-220AC Operating Temperature - Junction -65°C ~ 175°C	Series	FRED Pt?
Current - Average Rectified (Io) Voltage - Forward (Vf) (Max) @ If 1.05V @ 8A Speed Fast Recovery =< 500ns, > 200mA (Io) Reverse Recovery Time (trr) 250ns Current - Reverse Leakage @ Vr 5μA @ 600V Capacitance @ Vr, F Mounting Type Through Hole Package / Case TO-220-2 Supplier Device Package TO-220AC Operating Temperature - Junction 8A 1.05V @ 8A Fast Recovery =< 500ns, > 200mA (Io) 250ns Through Hole Through Hole To-220-2 Supplier Device Package TO-220AC -65°C ~ 175°C	Diode Type	Standard
Voltage - Forward (Vf) (Max) @ If1.05V @ 8ASpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	Voltage - DC Reverse (Vr) (Max)	600V
SpeedFast Recovery =< 500ns, > 200mA (Io)Reverse Recovery Time (trr)250nsCurrent - Reverse Leakage @ Vr5μA @ 600VCapacitance @ Vr, F-Mounting TypeThrough HolePackage / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction-65°C ~ 175°C	Current - Average Rectified (Io)	8A
Reverse Recovery Time (trr) 250ns Current - Reverse Leakage @ Vr 5 μ A @ 600V Capacitance @ Vr, F - Mounting Type Through Hole Package / Case TO-220-2 Supplier Device Package TO-220AC Operating Temperature - Junction -65°C ~ 175°C	Voltage - Forward (Vf) (Max) @ If	1.05V @ 8A
Current - Reverse Leakage @ Vr $5\mu A$ @ $600V$ Capacitance @ Vr, F - Mounting Type Through Hole Package / Case TO-220-2 Supplier Device Package TO-220AC Operating Temperature - Junction $-65^{\circ}C \sim 175^{\circ}C$	Speed	Fast Recovery =< 500ns, > 200mA (Io)
Capacitance @ Vr, F Mounting Type Through Hole Package / Case TO-220-2 Supplier Device Package TO-220AC Operating Temperature - Junction -65°C ~ 175°C	Reverse Recovery Time (trr)	250ns
Mounting Type Through Hole Package / Case TO-220-2 Supplier Device Package TO-220AC Operating Temperature - Junction Through Hole TO-220-2 TO-27-20-2 TO-27-20-2	Current - Reverse Leakage @ Vr	5μA @ 600V
Package / CaseTO-220-2Supplier Device PackageTO-220ACOperating Temperature - Junction -65° C ~ 175° C	Capacitance @ Vr, F	-
Supplier Device Package TO-220AC Operating Temperature - Junction -65°C ~ 175°C	Mounting Type	Through Hole
Operating Temperature - Junction $-65^{\circ}\text{C} \sim 175^{\circ}\text{C}$	Package / Case	TO-220-2
	Supplier Device Package	TO-220AC
Report errors?	Operating Temperature - Junction	-65°C ~ 175°C
		Report errors?

8ETL06 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8ETL06 Payment Methods





















8ETL06 Shipping Methods













If you have any question about 8ETL06, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com