

## **8L01-12-011 Information**



For Reference Only

Part Number 8L01-12-011
Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **8L01-12-011 Specifications**

Manufacturer Part Number8L01-12-011ManufacturerCoto TechnologyCategoryRelaysPackage-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps  - Series Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 1 ms Features Diode Mounting Type Termination Style Relays Relay Relays Relay Relays Relay Rela Rela Rela Rela Rela Rela Rela Rela	Manufacturer Part Number	8L01-12-011
Package-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Coto Technology
Package-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series         8L           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         12VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1 VDC           Operate Time         0.5ms           Release Time         Ims           Features         Diode           Mounting Type         Through Hole           Termination Style         PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time1 msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time1msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Series	8L
Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 1ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 1ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 1 Ims  Features Diode  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	24mA
Contact Rating (Current)  Switching Voltage  200VAC, 200VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1 VDC  Operate Time  0.5ms  Release Time  1 ms  Features  Diode  Mounting Type  Through Hole  Termination Style	Coil Voltage	12VDC
Switching Voltage  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1 VDC  Operate Time  0.5ms  Release Time  1ms  Features  Diode  Mounting Type  Through Hole  Termination Style	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9.6 VDC  1 VDC  Operate Time  0.5ms  Release Time  1 ms  Features  Diode  Mounting Type  Through Hole  Termination Style	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  O.5ms  Release Time  Ims  Features  Diode  Mounting Type  Through Hole  Termination Style  1 VDC  O.5ms  Ims  PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.5msRelease Time1msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9.6 VDC
Release Time 1ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1 VDC
Features Diode  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	0.5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	1ms
Termination Style PC Pin	Features	Diode
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **8L01-12-011 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 8L01-12-011 Payment Methods



















## **8L01-12-011 Shipping Methods**













If you have any question about 8L01-12-011, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com