

### 8L02-05-01 Information



For Reference Only

Part Number 8L02-05-01
Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **8L02-05-01 Specifications**

Manufacturer Part Number8L02-05-01ManufacturerCoto TechnologyCategoryRelaysPackage-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps  - Series Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage SvDC Contact Form DPST (2 Form A) Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 0.5ms Release Time Ims Features Mounting Type Through Hole Termination Style  Relays Redays Relays Relay Relays Relay Rela Rela Rela Rela Rela Rela Rela Rela	Manufacturer Part Number	8L02-05-01
Package-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Coto Technology
Package-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series         8L           Relay Type         Reed           Coil Type         Non Latching           Coil Current         25mA           Coil Voltage         5VDC           Contact Form         DPST (2 Form A)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         3.8 VDC           Turn Off Voltage (Min)         0.5 VDC           Operate Time         0.5ms           Release Time         Ims           Features         Diode           Mounting Type         Through Hole           Termination Style         PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease Time1msFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiodeMounting TypeThrough HoleTermination StylePC Pin	Series	8L
Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time 1ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time 1ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 3.8 VDC  Turn Off Voltage (Min) 0.5 VDC  Operate Time 0.5ms  Release Time 1ms  Features Diode  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	25mA
Contact Rating (Current)  Switching Voltage  200VAC, 200VDC - Max  Turn On Voltage (Max)  3.8 VDC  Turn Off Voltage (Min)  0.5 VDC  Operate Time  0.5ms  Release Time  1ms  Features  Diode  Mounting Type  Through Hole  Termination Style	Coil Voltage	5VDC
Switching Voltage  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Operate Time  Ims  Features  Diode  Mounting Type  Through Hole  Termination Style  200VAC, 200VDC - Max  3.8 VDC  0.5 VDC  0.5 WDC  0.5ms  Ims  PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  O.5ms  Release Time  Ims  Features  Diode  Mounting Type  Through Hole  Termination Style  3.8 VDC  0.5 VDC  Onerate Time  Ins  PC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  O.5 WDC  Operate Time  O.5ms  Release Time  Ims  Features  Diode  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time 0.5ms  Release Time 1ms  Features Diode  Mounting Type Through Hole  Termination Style PC Pin	Turn On Voltage (Max)	3.8 VDC
Release Time 1ms Features Diode Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Diode  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	0.5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	1ms
Termination Style PC Pin	Features	Diode
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### **8L02-05-01 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 8L02-05-01 Payment Methods



















### **8L02-05-01 Shipping Methods**













If you have any question about 8L02-05-01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com