

8L02-05-11 Information



For Reference Only

Part Number 8L02-05-11

Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8L02-05-11 Specifications

ManufacturerCoto TechnologyCategoryRelaysSegnal Relays, Up to 2 AmpsPackage-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic ShieldMounting TypeThrough HoleTermination StylePC Pin		
CategoryRelaysPackage-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease Time1msFeaturesDiode, Electrostatic ShieldMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	8L02-05-11
Package - Series 8L Relay Type Reed Coil Type Non Latching Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time Ims Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Coto Technology
Package-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic ShieldMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series8LRelay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic ShieldMounting TypeThrough HoleTermination StylePC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic ShieldMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current25mACoil Voltage5VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.8 VDCTurn Off Voltage (Min)0.5 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic ShieldMounting TypeThrough HoleTermination StylePC Pin	Series	8L
Coil Current 25mA Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time 1ms Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time 1ms Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time 1ms Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Coil Current	25mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.8 VDC Turn Off Voltage (Min) 0.5 VDC Operate Time 0.5ms Release Time 1ms Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Operate Time Ims Release Time Ims Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 3.8 VDC 0.5 VDC 0.5 ms Ims Peatures Diode, Electrostatic Shield PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Operate Time Ims Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style 3.8 VDC 0.5 VDC 0.5 ms Ims PC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time O.5 WDC Operate Time O.5ms Release Time Ims Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time 0.5ms Release Time 1ms Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	3.8 VDC
Release Time 1ms Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	0.5 VDC
Features Diode, Electrostatic Shield Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	1ms
Termination Style PC Pin	Features	Diode, Electrostatic Shield
·	Mounting Type	Through Hole
Danier	Termination Style	PC Pin
Report errors?		Report errors?

8L02-05-11 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8L02-05-11 Payment Methods



















8L02-05-11 Shipping Methods













If you have any question about 8L02-05-11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com