

## 8L21-12-00 Information



For Reference Only

Part Number 8L21-12-00
Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **8L21-12-00 Specifications**

Manufacturer Part Number         8L21-12-00           Manufacturer         Coto Technology           Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         8L           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         12VDC           Contact Form         SPST-NC (1 Form B)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1 VDC           Operate Time         0.5ms           Release Time         0.5ms           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin		
Category Relays Signal Relays, Up to 2 Amps  - Series Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 70 YOLT OPEN CONSTRUCT ON SPST-NC (1 Form B) Contact Rating (Current) Soma Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 70 YOLT OPEN CONSTRUCT ON SPST-NC (1 Form B) Contact Rating (Current) Soma Switching Voltage Contact Rating (Current) Soma Switching Voltage (Max) Somb Turn Off Voltage (Max) Somb Turn Off Voltage (Min) Type Through Hole Termination Style	Manufacturer Part Number	8L21-12-00
Package - Series 8L Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Coto Technology
Package-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series         8L           Relay Type         Reed           Coil Type         Non Latching           Coil Current         24mA           Coil Voltage         12VDC           Contact Form         SPST-NC (1 Form B)           Contact Rating (Current)         500mA           Switching Voltage         200VAC, 200VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1 VDC           Operate Time         0.5ms           Release Time         0.5ms           Features         -           Mounting Type         Through Hole           Termination Style         PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.5msFeatures-Mounting TypeThrough HoleTermination StylePC Pin	Series	8L
Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form SPST-NC (1 Form B) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 0.5ms Features - Mounting Type Through Hole Termination Style	Coil Type	Non Latching
Contact Form SPST-NC (1 Form B)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 0.5ms  Features - Mounting Type Through Hole  Termination Style PC Pin	Coil Current	24mA
Contact Rating (Current)  Switching Voltage  200VAC, 200VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1 VDC  Operate Time  0.5ms  Release Time  0.5ms  Features  - Mounting Type  Through Hole  Termination Style	Coil Voltage	12VDC
Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 0.5ms  Features -  Mounting Type Through Hole  Termination Style PC Pin	Contact Form	SPST-NC (1 Form B)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9.6 VDC  1 VDC  Operate Time  0.5ms  Release Time  0.5ms  Features  - Mounting Type  Through Hole  Termination Style	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  0.5ms  Release Time  0.5ms  Features  - Mounting Type  Through Hole  Termination Style  1 VDC  0.5ms  Through Hole  PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time 0.5ms  Release Time 0.5ms  Features	Turn On Voltage (Max)	9.6 VDC
Release Time 0.5ms  Features - Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1 VDC
Features - Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.5ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.5ms
Termination Style PC Pin	Features	-
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

### **8L21-12-00 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 8L21-12-00 Payment Methods



















## **8L21-12-00 Shipping Methods**













If you have any question about 8L21-12-00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com