

### **8L21-12-11 Information**



For Reference Only

Part Number 8L21-12-11
Manufacturer Coto Technology

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **8L21-12-11 Specifications**

ManufacturerCoto TechnologyCategoryRelaysPackage-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time1msFeaturesDiode, Electrostatic Shield		
CategoryRelaysPackage-Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time1msFeaturesDiode, Electrostatic Shield	Manufacturer Part Number	8L21-12-11
Package - Series 8L Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 1 ms Features Diode, Electrostatic Shield	Manufacturer	Coto Technology
Package - Series 8L Relay Type Reed Coil Type Non Latching Coil Current 24mA Coil Voltage 12VDC Contact Form SPST-NC (1 Form B) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.5ms Release Time 1ms Features Diode, Electrostatic Shield	Category	Relays
Series8LRelay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic Shield		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic Shield	Package	-
Coil TypeNon LatchingCoil Current24mACoil Voltage12VDCContact FormSPST-NC (1 Form B)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease TimeImsFeaturesDiode, Electrostatic Shield	Series	8L
Coil Current 24mA  Coil Voltage 12VDC  Contact Form SPST-NC (1 Form B)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 1ms  Features Diode, Electrostatic Shield	Relay Type	Reed
Coil Voltage 12VDC  Contact Form SPST-NC (1 Form B)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 1ms  Features Diode, Electrostatic Shield	Coil Type	Non Latching
Contact Form SPST-NC (1 Form B)  Contact Rating (Current) 500mA  Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 1 ms  Features Diode, Electrostatic Shield	Coil Current	24mA
Contact Rating (Current)  Switching Voltage  200VAC, 200VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1 VDC  Operate Time  0.5ms  Release Time  1ms  Features  Diode, Electrostatic Shield	Coil Voltage	12VDC
Switching Voltage 200VAC, 200VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1 VDC  Operate Time 0.5ms  Release Time 1ms  Features Diode, Electrostatic Shield	Contact Form	SPST-NC (1 Form B)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9.6 VDC  1 VDC  Operate Time  0.5 ms  Release Time  1 ms  Features  Diode, Electrostatic Shield	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  0.5ms  Release Time  1ms  Features  Diode, Electrostatic Shield	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.5msRelease Time1msFeaturesDiode, Electrostatic Shield	Turn On Voltage (Max)	9.6 VDC
Release Time 1ms Features Diode, Electrostatic Shield	Turn Off Voltage (Min)	1 VDC
Features Diode, Electrostatic Shield	Operate Time	0.5ms
	Release Time	1ms
	Features	Diode, Electrostatic Shield
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

#### **8L21-12-11 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **8L21-12-11 Payment Methods**

































If you have any question about 8L21-12-11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com