



8NLE2125E Information

Heisener.com

Part Number 8NLE2125E

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 125A 8.25KVAC

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8NLE2125E Specifications

Manufacturer Part Number8NLE2125EManufacturerLittelfuse Inc.CategoryCircuit ProtectionFlectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Manufacturer Part Number	8NLE2125E
PackageElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating125AVoltage Rating - AC8250V (8.25kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 125A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Package	Cartridge, Non-Standard
Current Rating 125A Voltage Rating - AC 8250V (8.25kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time Applications Transformer Protection Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 8250V (8.25kV) 8250V (8.25kV)	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Case - Case Cartridge, Non-Standard Size / Dimension - Case - Case Case Cartridge, Non-Standard Size / Dimension - Case Case Case Case Case Case Case Case	Current Rating	125A
Response Time	Voltage Rating - AC	8250V (8.25kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Transformer Protection Indicating E	Voltage Rating - DC	-
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Applications	Transformer Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Class	E
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)	Mounting Type	Holder
·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	17.875" L x 3.000" W x 6.380" H (454.03mm x 76.20mm x 162.05mm)
		Report errors?

8NLE2125E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8NLE2125E Payment Methods



















8NLE2125E Shipping Methods













If you have any question about 8NLE2125E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com