



8P1P00717BVL621 Information

s com

Part Number 8P1P00717BVL621 Manufacturer NorComp Inc.

Category Connectors, Interconnects
Circular Connectors

Description CONN PLUG MALE 7POS GOLD SOLDER

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









8P1P00717BVL621 Specifications

Manufacturer Part Number8PIP00717BVL621ManufacturerNorComp Inc.CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesQUIK-LOQ? 8PIPConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupPastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeaturesBackshell, Strain ReliefVoltage - Rated450VCurrent Rating6A		
Category Circular Connectors Package Package Connector Type Plug, Male Pins Pugh Male Pins Package Pree Hanging (In-Line) Pastening Type Push-Pull Pastening Type Push-Pull Porientation Keyed Ingress Protection Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Poltage - Rated Voltage - Rated Current Rating A Connectors, Interconnects Circular Connectors Circular Connectors Current Rating Circular Connectors Connectors Circular Connectors Cull Keyed Circular Connectors Circ	Manufacturer Part Number	8P1P00717BVL621
Circular Connectors Package - Series QUIK-LOQ? 8P1P Connector Type Plug, Male Pins Number of Positions 7 Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Manufacturer	NorComp Inc.
Package-SeriesQUIK-LOQ? 8P1PConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeaturesBackshell, Strain ReliefVoltage - Rated450VCurrent Rating6A	Category	Connectors, Interconnects
SeriesQUIK-LOQ? 8P1PConnector TypePlug, Male PinsNumber of Positions7Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeaturesBackshell, Strain ReliefVoltage - Rated450VCurrent Rating6A		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions7Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeaturesBackshell, Strain ReliefVoltage - Rated450VCurrent Rating6A	Package	-
Number of Positions7Shell Size - Insert-Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeaturesBackshell, Strain ReliefVoltage - Rated450VCurrent Rating6A	Series	QUIK-LOQ? 8P1P
Shell Size - Insert - Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Number of Positions	7
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeaturesBackshell, Strain ReliefVoltage - Rated450VCurrent Rating6A	Shell Size - Insert	-
Termination Solder Cup Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Shell Size, MIL	-
Fastening Type Push-Pull Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Mounting Type	Free Hanging (In-Line)
Orientation Keyed Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Termination	Solder Cup
Ingress Protection IP50 - Dust Protected Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Fastening Type	Push-Pull
Shell Material, Finish Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC) Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Orientation	Keyed
Contact Finish Gold Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Ingress Protection	IP50 - Dust Protected
Features Backshell, Strain Relief Voltage - Rated 450V Current Rating 6A	Shell Material, Finish	Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)
Voltage - Rated 450V Current Rating 6A	Contact Finish	Gold
Current Rating 6A	Features	Backshell, Strain Relief
•	Voltage - Rated	450V
Report errors?	Current Rating	6A
		Report errors?

8P1P00717BVL621 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

8P1P00717BVL621 Payment Methods



















8P1P00717BVL621 Shipping Methods













If you have any question about 8P1P00717BVL621, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com