

# 8P1P010210ARBR1

#### 8P1P010210ARBR1 Information

Heisener.com	Part Number Manufacturer Category Description Package	8P1P010210ARBR1 NorComp Inc. Connectors, Interconnects Circular Connectors CONN RCPT FMALE 10POS GOLD SOLDR - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 8P1P010210ARBR1 Specifications

Manufacturer Part NumberPIP10210ARBR1ManufacturerNorComp Inc.CategoryConnectorsPackage-PackageQUIK-LOQ? 8P1PConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleNorentationSolderStening TypeUSA-DUIL PolicyNeger SprotectionSolderShell Size, FinishSolderStening TypeSolderStening TypeSolder<				
CategoryConcerts interconnectsCategoryConnectors, InterconnectsPackage-Package-SeriesQUIK-LOQ? 8P1PConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact Finish-Voltage - Rated333VCurrent Rating3A	Manufacturer Part Number	8P1P010210ARBR1		
Initial ConnectorsPackage-SeriesQUIK-LOQ? SPIPConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationIF90 - Dust ProtectedShell Material, FinishOldaGoldGoldFeatures-Voltage - Rated333VCurrent Rating3A	Manufacturer	NorComp Inc.		
Package.SeriesQUK-LOQ? 8P1PConector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert.Shell Size, MIL.Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypeNush-PullOrientationKeyedShell Material, FinishPolyacrytoneted (ASS), Polycarbonate (PC)Shell Material, FinishGoldFastense.Yoltage-Rated333VCurrent RatingSaleShell Material, FinishSaleSolder.Statering Type.Statering StateringSolderStatering Statering.Statering Statering. <td>Category</td> <td colspan="3">Connectors, Interconnects</td>	Category	Connectors, Interconnects		
SeriesQUIK-LOQ? 8P1PConnector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldYoltage - Rated333VCurrent Rating3A		Circular Connectors		
Connector TypeReceptacle, Female SocketsNumber of Positions10Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Shell Material, FinishGoldFeatures-Voltage - Rated333VCurrent RatingSal	Package	-		
Number of Positions10Shell Size - Insert-Shell Size, MIL-Mountig TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact Finish-Features-Voltage - Rated333VCurrent Rating3A	Series	QUIK-LOQ? 8P1P		
Shell Size - Insert-Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Features-Voltage - Rated333VCurrent Rating3A	Connector Type	Receptacle, Female Sockets		
Shell Size, MIL-Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact Finish-Features-Voltage - Rated333VCurrent Rating3A	Number of Positions	10		
Mounting TypePanel Mount, Bulkhead; Through Hole, Right AngleTerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeatures-Voltage - Rated333VCurrent RatingSA	Shell Size - Insert	-		
TerminationSolderFastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeatures-Voltage - Rated333VCurrent Rating3A	Shell Size, MIL	-		
Fastening TypePush-PullOrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeatures-Voltage - Rated333VCurrent Rating3A	Mounting Type	Panel Mount, Bulkhead; Through Hole, Right Angle		
OrientationKeyedIngress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeatures-Voltage - Rated333VCurrent Rating3A	Termination	Solder		
Ingress ProtectionIP50 - Dust ProtectedShell Material, FinishPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeatures-Voltage - Rated333VCurrent Rating3A	Fastening Type	Push-Pull		
SolutionPolyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)Contact FinishGoldFeatures-Voltage - Rated333VCurrent Rating3A	Orientation	Keyed		
Contact FinishGoldFeatures-Voltage - Rated333VCurrent Rating3A	Ingress Protection	IP50 - Dust Protected		
Features-Voltage - Rated333VCurrent Rating3A	Shell Material, Finish	Polyacrylonitrile Butadiene Styrene (ABS), Polycarbonate (PC)		
Voltage - Rated333VCurrent Rating3A	Contact Finish	Gold		
Current Rating 3A	Features	-		
C	Voltage - Rated	333V		
Report errors?	Current Rating	3A		
		Report	errors?	

#### 8P1P010210ARBR1 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 8P1P010210ARBR1 Payment Methods





If you have any question about 8P1P010210ARBR1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com