

9-1393243-2 Information



For Reference Only

Part Number 9-1393243-2

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPDT 8A 115V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9-1393243-2 Specifications

Manufacturer Part Number 9-1393243-2 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Power Relays, Over 2 Amps Package - Series RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 6.6mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole		
CategoryRelaysPackage-SeriesRT2, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.6mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough Hole	Manufacturer Part Number	9-1393243-2
Package - Series RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 6.6mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Turn On Poltage (Max) Through Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series RT2, SCHRACK Relay Type General Purpose Coil Type Non Latching Coil Current 6.6mA Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Category	Relays
SeriesRT2, SCHRACKRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.6mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current6.6mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current6.6mACoil Voltage115VACContact FormDPDT (2 Form C)Contact Rating (Current)8ASwitching Voltage400VAC - MaxTurn On Voltage (Max)86.3 VACTurn Off Voltage (Min)17.3 VACOperate Time-Release Time-FeaturesInsulation - Class F, Sealed - Flux ProtectionMounting TypeThrough Hole	Series	RT2, SCHRACK
Coil Current Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Relay Type	General Purpose
Coil Voltage 115VAC Contact Form DPDT (2 Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Coil Type	Non Latching
Contact Form C) Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Coil Current	6.6mA
Contact Rating (Current) 8A Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Coil Voltage	115VAC
Switching Voltage 400VAC - Max Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 86.3 VAC Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Contact Rating (Current)	8A
Turn Off Voltage (Min) 17.3 VAC Operate Time Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Switching Voltage	400VAC - Max
Operate Time - Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Turn On Voltage (Max)	86.3 VAC
Release Time - Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Turn Off Voltage (Min)	17.3 VAC
Features Insulation - Class F, Sealed - Flux Protection Mounting Type Through Hole	Operate Time	-
Mounting Type Through Hole	Release Time	-
	Features	Insulation - Class F, Sealed - Flux Protection
m 1 1 2 2 1	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

9-1393243-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9-1393243-2 Payment Methods



















9-1393243-2 Shipping Methods













If you have any question about 9-1393243-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com