

9-1415536-1 Information

Heisener.com

Part Number 9-1415536-1

Manufacturer TE Connectivity Potter & Brumfield Relays

Category

Power Relays, Over 2 Amps

Description RELAY SAFETY DPDT 6A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9-1415536-1 Specifications

Manufacturer Part Number Manufacturer TE Connectivity Potter & Brumfield Relays Relays Power Relays, Over 2 Amps Package Series SR2Z, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max
Category Relays Power Relays, Over 2 Amps Package Series SR2Z, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max
Package Series SR2Z, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) Switching Voltage 250VAC - Max
Package - Series SR2Z, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Series SR2Z, SCHRACK Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Relay Type General Purpose with Socket Coil Type Non Latching Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Coil TypeNon LatchingCoil Current29.2mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)6ASwitching Voltage250VAC - Max
Coil Current 29.2mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Contact Form DPDT (2 Form C) Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Contact Rating (Current) 6A Switching Voltage 250VAC - Max
Switching Voltage 250VAC - Max
Turn On Voltage (Max) 21.6 VDC
Turn Off Voltage (Min) 2.4 VDC
Operate Time -
Release Time -
Features -
Mounting Type DIN Rail
Termination Style Screwless Clamp
Report errors?

9-1415536-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9-1415536-1 Payment Methods



















9-1415536-1 Shipping Methods













If you have any question about 9-1415536-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com