

9001-05-10 Information



For Reference Only

Part Number 9001-05-10 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9001-05-10 Specifications

Manufacturer Part Number 9001-05-10 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 10mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	-	
Category Relays Signal Relays, Up to 2 Amps - Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 10mA Coil Voltage SyDC Contact Form SpST-NO (1 Form A) Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Termination Style	Manufacturer Part Number	9001-05-10
Package - Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 10mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Manufacturer	Coto Technology
Package-Series9000Relay TypeReedCoil TypeNon LatchingCoil Current10mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 10mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current10mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current10mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Series	9000
Coil Current Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Coil Current	10mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style	Coil Voltage	5VDC
Switching Voltage 200VAC, 200VDC - Max 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.35ms Release Time 0.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 3.75 VDC 0.4 VDC 0.4 VDC 0.7 Turn Off Voltage (Min) 0.8 Turn Off Voltage (Min) 0.9 Turn Off Voltage (Min) 0.	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time O.35ms Release Time O.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style 3.75 VDC 0.4 VDC 0.35ms Release Time O.1ms Features Magnetic Shield PC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time O.35ms Release Time O.1ms Features Magnetic Shield Mounting Type Through Hole Termination Style O.4 VDC O.35ms Release Time O.1ms PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.35msRelease Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	3.75 VDC
Release Time0.1msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	0.4 VDC
Features Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.35ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.1ms
Termination Style PC Pin	Features	Magnetic Shield
·	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

9001-05-10 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9001-05-10 Payment Methods





















9001-05-10 Shipping Methods













If you have any question about 9001-05-10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com