

9001-12-11 Information

Heisener.com

Part Number 9001-12-11
Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED SPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9001-12-11 Specifications

Manufacturer Part Number 9001-12-11 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole		
Category Relays Signal Relays, Up to 2 Amps Package Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 7 urn Off Voltage (Min) Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type	Manufacturer Part Number	9001-12-11
Package Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Series 9000 Reed 12VDC Non Latching 12VDC 0000 Non Latching 12VDC 0000 0000 0000 0000 0000 0000 00000 0000	Manufacturer	Coto Technology
Package - Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Category	Relays
Series 9000 Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Trhrough Hole		Signal Relays, Up to 2 Amps
Relay Type Reed Coil Type Non Latching Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Trhrough Hole	Package	-
Coil Type Coil Current 12mA Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Series	9000
Coil Current Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Relay Type	Reed
Coil Voltage 12VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Coil Current	12mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Coil Voltage	12VDC
Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.35ms Release Time 0.1ms Features Diode, Magnetic Shield Mounting Type Through Hole	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.35msRelease Time0.1msFeaturesDiode, Magnetic ShieldMounting TypeThrough Hole	Turn On Voltage (Max)	9 VDC
Release Time0.1msFeaturesDiode, Magnetic ShieldMounting TypeThrough Hole	Turn Off Voltage (Min)	1 VDC
Features Diode, Magnetic Shield Mounting Type Through Hole	Operate Time	0.35ms
Mounting Type Through Hole	Release Time	0.1ms
	Features	Diode, Magnetic Shield
The state of the s	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

9001-12-11 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9001-12-11 Payment Methods



















9001-12-11 Shipping Methods













If you have any question about 9001-12-11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com