

9007-12-10

9007-12-10 Information

Heisener.com	Part Number Manufacturer Category Description Package	9007-12-10 Coto Technology Relays Signal Relays, Up to 2 Amps RELAY REED SPST 500MA 12V - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



9007-12-10 Specifications

Manufacturer Part Number 9007-12-10 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Signal Relays, Up to 2 Amps Package - Stries 9000, Spartan Relay Type Red Coil Type Non Latching Coil Current 12mA Coil Acting Current) SPST-NO (I Form A) Contact Form SOWAA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Operate Time 0.5ms Release Time 0.2ms Features Magnetic Shield Mounting Type PC Pin		
CategoryRelaysSaignal Relays, Up to 2 AmpsPackagePackageSeries9000, SpartanRelay TypeRelay TypeCoil TypeNon LatchingCoil Current12mACoil VoltageContact FormSomASomASutching VoltageSwitching VoltageSutching Voltage (Max)Yun On Voltage (Max)Operate TimeRelease TimeFeaturesMounting TypeTermination StyleVertination StyleStation Style <tr< td=""><td>Manufacturer Part Number</td><td>9007-12-10</td></tr<>	Manufacturer Part Number	9007-12-10
Signal Relays, Up to 2 AmpsPackage-Series9000, SpartanRelay TypeReedCoil TypeNon LatchingCoil Current12mAColt ActionSPST-NO (1 Form A)Contact FormSUVDC - MaxContact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StyleCP in	Manufacturer	Coto Technology
Package-Series9000, SpartanRelay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeCri PrinTermination StyleCP Fin	Category	Relays
Series9000, SpartanRelay TypeReedCoil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)S00MASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypePC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LachingCoil Current12mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage (Max)9 VDC - MaxTurn On Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current12mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Man)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypePC Pin	Series	9000, Spartan
Coil Current12mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeFrough HoleTermination StylePC Pin	Relay Type	Reed
Coil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Form500mAContact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Coil Current	12mA
Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleFermination StylePC Pin	Coil Voltage	12VDC
Switching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleFermination StylePC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Contact Rating (Current)	500mA
Turn Off Voltage (Min)1 VDCOperate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.5msRelease Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9 VDC
Release Time0.2msFeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	1 VDC
FeaturesMagnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Operate Time	0.5ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	0.2ms
Termination Style PC Pin	Features	Magnetic Shield
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

9007-12-10 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE SUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 9007-12-10, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com