

# 9016-0-15-15-07-27-10-0

### 9016-0-15-15-07-27-10-0 Information

A CONTRACTOR	 9016-0-15-15-07-27-10-0 Mill-Max Manufacturing Corp. Connectors, Interconnects Terminals - PC Pin Receptacles, Socket Connectors CONN PIN RCPT .065082 PRESSFIT - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 9016-0-15-15-07-27-10-0 Specifications

Manufacturer Part Number9016-0-15-15-07-27-10-0ManufacturerMill-Max Manufacturing Corp.CategoryConnectors, InterconnectsTerminals - PC Pin Receptacles, Socket ConnectorsPackage-Series9016Tail TypeNo TailTerminationPress-FitLength - Overall0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.101" (2.72mm)Pin Hole Diameter0.107" (2.72mm)Filange Diameter0.107" (4.37mm)Tail Diameter0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30jui (0.76µm)		
CategoryConnectors, Interconnects Terminals - PC Pin Receptacles, Socket ConnectorsPackage-Series9016Tail TypeNo TailTerminationPress-FitLength - Overall0.240" (6.10mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.172" (4.37mm)Tail Diameter-Socket Depth0.240" (6.10mm)Contact KinshGoldGondart FinishGoldContact Finish Thickness30µin (0.76µm)	Manufacturer Part Number	9016-0-15-15-07-27-10-0
Terminals - PC Pin Receptacles, Socket ConnectorsPackage-Series9016Tail TypeNo TailTerminationPress-FitLength - Overall0.240" (6.10mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter-Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)	Manufacturer	Mill-Max Manufacturing Corp.
Package-Series9016Tail TypeNo TailTerminationPress-FitLength - Overall0.240" (6.10mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter0.240" (6.10mm)Contact Material0.240" (6.10mm)Contact FinishGoldContact Finish Thickness30µin (0.76µm)	Category	Connectors, Interconnects
Series9016Tail TypeNo TailTerminationPress-FitLength - Overall0.240" (6.10mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter0.240" (6.10mm)Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldSourd Finish Thickness30µin (0.76µm)		Terminals - PC Pin Receptacles, Socket Connectors
Tail TypeNo TailTerminationPress-FitLength - Overall0.240" (6.10mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter0.240" (6.10mm)Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)	Package	-
TerminationPress-FitLength - Overall0.240" (6.10mm)Accepts Pin Diameter0.065" ~ 0.082" (1.65mm ~ 2.08mm)Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter-Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact Finish Thickness30µin (0.76µm)	Series	9016
Length - Overall   0.240" (6.10mm)     Accepts Pin Diameter   0.065" ~ 0.082" (1.65mm ~ 2.08mm)     Mounting Hole Diameter   0.131" (3.33mm)     Pin Hole Diameter   0.107" (2.72mm)     Flange Diameter   0.172" (4.37mm)     Tail Diameter   -     Socket Depth   0.240" (6.10mm)     Contact Material   Beryllium Copper     Contact Finish   Gold     Contact Finish Thickness   30µin (0.76µm)	Tail Type	No Tail
Accepts Pin Diameter 0.065" ~ 0.082" (1.65mm ~ 2.08mm)   Mounting Hole Diameter 0.131" (3.33mm)   Pin Hole Diameter 0.107" (2.72mm)   Flange Diameter 0.172" (4.37mm)   Tail Diameter -   Socket Depth 0.240" (6.10mm)   Contact Material Beryllium Copper   Contact Finish Gold   Contact Finish Thickness 30µin (0.76µm)	Termination	Press-Fit
Mounting Hole Diameter0.131" (3.33mm)Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter-Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Length - Overall	0.240" (6.10mm)
Pin Hole Diameter0.107" (2.72mm)Flange Diameter0.172" (4.37mm)Tail Diameter-Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Accepts Pin Diameter	0.065" ~ 0.082" (1.65mm ~ 2.08mm)
Flange Diameter0.172" (4.37mm)Tail Diameter-Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Mounting Hole Diameter	0.131" (3.33mm)
Tail Diameter-Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Pin Hole Diameter	0.107" (2.72mm)
Socket Depth0.240" (6.10mm)Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30µin (0.76µm)	Flange Diameter	0.172" (4.37mm)
Contact MaterialBeryllium CopperContact FinishGoldContact Finish Thickness30μin (0.76μm)	Tail Diameter	-
Contact FinishGoldContact Finish Thickness30µin (0.76µm)	Socket Depth	0.240" (6.10mm)
Contact Finish Thickness 30µin (0.76µm)	Contact Material	Beryllium Copper
	Contact Finish	Gold
Report errors?	Contact Finish Thickness	30µin (0.76µm)
		Report errors?

#### 9016-0-15-15-07-27-10-0 Guarantees




**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.





If you have any question about 9016-0-15-15-07-27-10-0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com