

9092-12-11 Information



For Reference Only

Part Number 9092-12-11 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY REED DPST 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9092-12-11 Specifications

Manufacturer Part Number9092-12-11ManufacturerCoto TechnologyCategoryRelaysPackage-Series9092Relay TypeReedCoil TypeNon LatchingCoil Current16mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.5msFeaturesDiode, Magnetic ShieldMounting TypeThrough HoleTermination StylePC Pin		
Category Relays Signal Relays, Up to 2 Amps - Series 9092 Relay Type Reed Coil Type Non Latching Coil Current 16mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Termination Style	Manufacturer Part Number	9092-12-11
Package-Series9092Relay TypeReedCoil TypeNon LatchingCoil Current16mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.5msFeaturesDiode, Magnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Coto Technology
Package-Series9092Relay TypeReedCoil TypeNon LatchingCoil Current16mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.5msFeaturesDiode, Magnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series 9092 Relay Type Reed Coil Type Non Latching Coil Current 16mA Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin		Signal Relays, Up to 2 Amps
Relay TypeReedCoil TypeNon LatchingCoil Current16mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.5msFeaturesDiode, Magnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Package	-
Coil TypeNon LatchingCoil Current16mACoil Voltage12VDCContact FormDPST (2 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)9 VDCTurn Off Voltage (Min)1 VDCOperate Time0.75msRelease Time0.5msFeaturesDiode, Magnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Series	9092
Coil Current Coil Voltage 12VDC Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Relay Type	Reed
Coil Voltage Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form DPST (2 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Coil Current	16mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style	Coil Voltage	12VDC
Switching Voltage Turn On Voltage (Max) 9 VDC Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style 200VAC, 200VDC - Max 9 VDC 1 VDC 0.75ms PC Pin	Contact Form	DPST (2 Form A)
Turn On Voltage (Max) 7 Turn Off Voltage (Min) 1 VDC Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.75ms Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	200VAC, 200VDC - Max
Operate Time0.75msRelease Time0.5msFeaturesDiode, Magnetic ShieldMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	9 VDC
Release Time 0.5ms Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	1 VDC
Features Diode, Magnetic Shield Mounting Type Through Hole Termination Style PC Pin	Operate Time	0.75ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	0.5ms
Termination Style PC Pin	Features	Diode, Magnetic Shield
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

9092-12-11 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9092-12-11 Payment Methods



















9092-12-11 Shipping Methods













If you have any question about 9092-12-11, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com