

### **90FE Information**

www.heisener.com

For Reference Only

**Part Number** 90FE **Manufacturer** Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 90A 450VDC CYLINDR

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









OUEE	<b>Specifications</b>
<b>YUF E</b>	Specifications

Manufacturer Part Number  Manufacturer  Eaton  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  Series  FE  Fuse Type  Cartridge  Current Rating  90A  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Protection  Seport errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFEFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC-Voltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Manufacturer Part Number	90FE
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFEFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC-Voltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFEFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC-Voltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Category	Circuit Protection
SeriesFEFuse TypeCartridgeCurrent Rating90AVoltage Rating - AC-Voltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating90AVoltage Rating - AC-Voltage Rating - DC450VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 90A  Voltage Rating - AC -  Voltage Rating - DC 450V  Response Time -  Applications Electrical, Industrial  Features -  Class -  Approvals CE, UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Series	FE
Voltage Rating - AC  Voltage Rating - DC  450V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Size / Dimension  - Class  - Class  CE, UR  COLUR  C	Fuse Type	Cartridge
Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features - Class - Approvals CE, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  450V  450V  450V  450V  450V  450V  60V  60V  60V  60V  60V  60V  60V	Current Rating	90A
Response Time - Gettrical, Industrial - Gettrical, Industrical - Gettrical, Industrial - Gettrical, In	Voltage Rating - AC	-
Applications Electrical, Industrial  Features - Class - Approvals CE, UR  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Voltage Rating - DC	450V
Features - Class - Class - CE, UR  Approvals CE, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Response Time	-
Class - CE, UR  Operating Temperature - Streaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension O.673" Dia x 1.890" L (17.10mm x 48.00mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Approvals	CE, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.673" Dia x 1.890" L (17.10mm x 48.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.673" Dia x 1.890" L (17.10mm x 48.00mm)
Topoli Milato		Report errors?

### **90FE Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **90FE Payment Methods**



















# 90FE Shipping Methods













If you have any question about 90FE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com