

91596-008TR

91596-008TR Information

Heisener.com		91596-008TR Amphenol FCI Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN RCPT 8POS SMD B/E GOLD	
For Reference Only	C	For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



91596-008TR Specifications

Manufacturer Part Number91596-008TRManufacturerAmphenol FCICategoryConnectors, InterconnectsPackage-Package-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSuface MountMounting TypeSuface MountFerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - MatingGoldIsuulation ColorBlack		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeBoard to Board or CableStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderFarminationSolderFarening TypeGoldContact Finish - MatingGoldContact Finish - MatingBiak	Manufacturer Part Number	91596-008TR
Package-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderFerminationSolderFastening TypeOod (Gual Cable)Forth - MatingSolderInterninationSolderForth Strikenses - MatingBin (0.20µm)Fastening TypeBin (0.20µm)Fastening TypeBin (0.20µm)Contact Finish Thickness - MatingBiak	Manufacturer	Amphenol FCI
Package-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldInsulation ColorBlack	Category	Connectors, Interconnects
SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountFastening TypeSolderFastening TypeSolderContact Finish - MatingGoldInsulation ColorBlack	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIonater Finish - MatingBiak	Series	Minitek?
StyleBoard to Board or CableNumber of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIonat Finish Thickness - MatingBiack	Connector Type	Receptacle, Bottom Entry
Number of Positions8Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKonster Ser MatingBiak	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlack	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingSign (0.20µm)Konta ColorBlack	Number of Positions	8
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish Thickness - MatingBµin (0.20µm)Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish Thickness - MatingBjan (0.20µm)BackBlack	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Matingβμin (0.20μm)Insulation ColorBlack	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating8μin (0.20μm)Insulation ColorBlack	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating8μin (0.20μm)Insulation ColorBlack	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating8µin (0.20µm)Insulation ColorBlack	Termination	Solder
Contact Finish Thickness - Mating8μin (0.20μm)Insulation ColorBlack	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	8µin (0.20µm)
Insulation Height 0.001" (2.30mm)	Insulation Color	Black
0.071 (2.50mm)	Insulation Height	0.091" (2.30mm)
Contact Length - Post -	Contact Length - Post	-
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	Pick and Place	
	Demost energy	

Report errors?

91596-008TR Guarantees **Quality Guarantees** We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SFRVIO We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. 91596-008TR Payment Methods WIRE transfer Ҏ PayPal ၍ MoneyGram <u>Alipay</u> VISA DISCOVER 91596-008TR Shipping Methods

If you have any question about 91596-008TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com