

# 91596-124TR

## 91596-124TR Information

Heisener.com	Part Number Manufacturer Category Description Package	91596-124TR Amphenol FCI Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN RCPT 24POS SMD B/E GOLD	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 91596-124TR Specifications

Manufacturer Part Number91596-124TRManufacturerAmphenol FCICategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPich - Mating0.079" (2.00mn)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypeSurface MountContact Finish - MatingGoldContact Finish Thickness - MatingJojin (0.76µm)Insulation ColorBlackInsulation Fleight0.091" (2.00mn)Contact Finish Thickness - MatingSolderContact Finish Thickness - MatingJojin (0.76µm)Contact Finish Thickness - MatingJojin (0.76µm)Contact Length - Post-Contact Length - Post-Contact Length - Post-Contact Finish ThicknessJuly -U		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeBoard to Board or CableStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows2Row Spacing - MatingSolderMounting TypeSurface MountFreminationSolderFastening TypeGoldContact Finish - MatingJouin (0.76µm)Insulation ColorBlackInsulation FlexesJouin (0.76µm)Insulation FlexesJouin (0.76µm)Insulation FlexesSolderInsulation FlexesSolderInsulation FlexesSolderInsulation FlexesJouin (0.76µm)Insulation FlexesJouin (0.76µm)Insulation FlexesSolderInsulation FlexesSolder	Manufacturer Part Number	91596-124TR
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountYardee MountSolderTerminationSolderFastening TypeOuslContact Finish - MatingGoldContact Finish Thickness - MatingJujin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Sperating Temperature-55°C ~ 125°C	Manufacturer	Amphenol FCI
Package-SeriesMintek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows2Row Spacing - Mating0.079° (2.00mm)Mounting Type0.079° (2.00mm)Yenning TypeSolderForminationSolderForning TypeSolderContact Finish - MatingGoldContact Finish - MatingJoin (0.76µm)Insulation ColorBlackInsulation Height0.091° (2.30mm)Forning TypeSolderInsulation Height0.91° (2.30mm)Solder Contact Finish TypeSolderSolder Contact Finish TypeSolder	Category	Connectors, Interconnects
SeriesMinitek?Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderFerminationSolderFortart Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingBiakInsulation ColorBiackInsulation Finish0.091" (2.30mm)Contact Length - Post-Contact Length - Post-Solart Time SolartSigner SolartInsulation Height0.991" (2.30mm)Contact Length - Post-Solart Time SolartSigner SolartSolart Finish Time Solart </td <td></td> <td>Rectangular Connectors - Headers, Receptacles, Female Sockets</td>		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (.00mm)Number of Rows2Row Spacing - Mating0.079" (.00mm)Mounting TypeSolderTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.091" (.30mm)Contact Length - Post.55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Sperating Temperature55°C ~ 125°C	Series	Minitek?
StyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Connector Type	Receptacle, Bottom Entry
Number of Positions 24   Number of Positions Loaded All   Number of Positions Loaded 0.079" (2.00mm)   Pitch - Mating 0.079" (2.00mm)   Number of Rows 2   Row Spacing - Mating 0.079" (2.00mm)   Mounting Type Surface Mount   Termination Solder   Fastening Type Push-Pull   Contact Finish - Mating Gold   Insulation Color Black   Insulation Height 0.091" (2.30mm)   Contact Length - Post -   Operating Temperature -55°C ~ 125°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.091" (2.30mm)Contact Length - Post-Contact Length - Post-Solcer-Solcer-Soltart Soltart - Soltar	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.091" (2.30mm)Contact Length - Post-55°C ~ 125°C	Number of Positions	24
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.091" (2.30mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.091" (2.30mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead
Mated Stacking Heights	-
Ingress Protection	-
Features	Pick and Place



DISCOVER

# 91596-124TR Guarantees **Quality Guarantees** We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition. **Service Guarantees** SFRVI We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers. 91596-124TR Payment Methods WIRE transfer Ҏ PayPal ၍ MoneyGram <u>Alipay</u> VISA 91596-124TR Shipping Methods FedEx. 🚳 CRT

If you have any question about 91596-124TR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com