

91614-421LF

equest a Quote

91614-421LF Information

Heisener.com	Part Number	91614-421LF
	Manufacturer	Amphenol FCI
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
	Description	CONN RCPT 21POS .100 SGL STR SMD
	Package	-
or Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



91614-421LF Specifications

Manufacturer Part Number91614-211.FManufacturerAmphenol FCICategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Contact TypeReceptacle, Bottom or Top EntryContact TypeBoard to BoardNumber of Positions21Number of Positions LoadedAllPich - Mating0.100° (2.54mm)Number of Rows1Number of RowsSurface MountYerninationSolderFerninationSolderFortact Finish - MatingSolderContact Finish - MatingTinContact Finish - MatingCongrammentSoltari Finish - MatingContact Finish - MatingContact Finish - MatingCoract CongrammentContact Finish Thickness - MatingCoract CongrammentContact Length - PostCoract CongrammentContact Length - Post-Material Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllNumber of Rows1Number of Rows1Number of RowsSolderStyleSolderFerninationSolderFerninationSolderContact Finish - Mating1%Contact Finish - Mating7%Sundion ColorGrayInsulation ColorGrayInsulation Finish Thickness - Mating0.275" (6.99mm)Contact Length - Post-Operating Temperature-Operating Temperature-	Manufacturer Part Number	91614-421LF
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - MatingSurface MountYingSurface MountFerminationSolderFastening TypePush-PullContact Finish - Mating7inContact Finish Thickness - Mating6rayInsulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Manufacturer	Amphenol FCI
Package-SeriesDubox?Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllPich - Mating0.100° (2.54mm)Number of Rows1Row Spacing - MatingSurface MountYerminationSurface MountTerminationSolderFortact Frinking MatingSolderContact Finish - MatingTinContact Finish - MatingRoy Spacing - MatingInsulation ColorGrayInsulation Finish - MatingSolderInsulation Finish - Mati	Category	Connectors, Interconnects
SeriesDubox?Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - MatingSolderMounting TypeSolderFerminationSolderFortar Finish - MatingSolderContact Finish - MatingTinContact Finish - MatingRow Spacing - MatingInsulation ColorGrayInsulation Finish - MatingSolderFinish - MatingSolderContact Finish - MatingSolderInsulation Finish - Mating		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountFerminationSolderContact Finish - Mating10Contact Finish - MatingSinface MountFornat Finish Thickness - MatingSinface MountInsulation ColorGrayInsulation Height0.25" (6.99mm)Contact Funish - Post-Storage Theorem-Storage Theorem-Storage Theorem-Storage Theorem-Storage Theorem-Storage Theorem-Storage Theorem-Storage Thing Thickness - Mating-Storage Theorem-Storage Theorem- <t< td=""><td>Package</td><td>-</td></t<>	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.0µm)Insulation ColorGrayInsulation Height0.275° (6.99mm)Contact Fungerature-Operating Temperature-	Series	Dubox?
StyleBoard to BoardStyleBoard to BoardNumber of Positions21Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Connector Type	Receptacle, Bottom or Top Entry
Number of Positions21Number of Positions LoadedAllNumber of Positions Loaded0.100" (2.54mm)Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Row Spacing - MatingSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-Operating Temperature-	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - MatingGrayInsulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-Operating Temperature-Operature- <t< td=""><td>Number of Positions</td><td>21</td></t<>	Number of Positions	21
Number of Rows1Row Spacing - Mating-Hounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - MatingRoyInsulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-Insulation ColorSurface MotingInsulation Height-Surface Mating-Surface Mating- <td>Number of Positions Loaded</td> <td>All</td>	Number of Positions Loaded	All
Row Spacing - Mating-Row Spacing - MatingSurface MountMounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Pitch - Mating	0.100" (2.54mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Number of Rows	1
TerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7μin (2.00μm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Mounting Type	Surface Mount
Contact Finish - MatingTinContact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Termination	Solder
Contact Finish Thickness - Mating78.7µin (2.00µm)Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Fastening Type	Push-Pull
Insulation ColorGrayInsulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Contact Finish - Mating	Tin
Insulation Height0.275" (6.99mm)Contact Length - Post-Operating Temperature-	Contact Finish Thickness - Mating	78.7µin (2.00µm)
Contact Length - Post-Operating Temperature-	Insulation Color	Gray
Operating Temperature -	Insulation Height	0.275" (6.99mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	-
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	10.81mm
Ingress Protection	-
Features	Board Lock

Report errors?

91614-421LF Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 91614-421LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com