

# 91625-317LF

equest a Quote

## 91625-317LF Information

Contraction for the second sec	Part Number	91625-317LF
	Manufacturer	Amphenol FCI
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
	Description	CONN RCPT 24POS T/H 2.54MM AU
	Package	-
For Reference Only		For the pricing/inventory/lead time, please contact
		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 91625-317LF Specifications

Manufacturer Part Number91625-317LFManufacturerAmphenol FCICategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Contact TypeReceptacleContact TypeReceptacleStyleBoardNumber of Positions24Number of Positions Loaded0Pich - Mating0.100° (2.54mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish Thickness - MatingSolderStulation ColorBueInsulation ColorBueInsulation Height0.335° (8.51mm)Contact Length - Post0.118° (3.00mm)Contact Length - Post111.94 v_O		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQui (0.76µm)Contact Finish - MatingGoldContact Finish Thickness - MatingJouin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Manufacturer Part Number	91625-317LF
ActageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeOlderTerminationSolderFastening TypeQuid (0.54mm)Contact Finish - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlueInsulation Height0.335° (8.51mm)Contact Length - Post0.118° (3.00mm)Operating Temperature-	Manufacturer	Amphenol FCI
Package-SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting Type0.100° (2.54mm)Yourge TypeSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJoin (0.76µm)Insulation ColorBlueInsulation Height0.335° (8.51nm)Contact Length - Post0.118° (3.00mm)Operating Temperature-	Category	Connectors, Interconnects
SeriesDubox?Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingSolidor (S.fum)Insulation ColorBlueInsulation Height0.33" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeMolor (2.54mm)TerminationSolderFastening TypeVesh-PullContact Finish - MatingGoldInsulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Series	Dubox?
StyleBoard to BoardStyleBoard to BoardNumber of Positions24Number of Positions Loaded10Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Connector Type	Receptacle
Number of Positions 24   Number of Positions Loaded 10   Number of Positions Loaded 0.100" (2.54mm)   Pitch - Mating 0.100" (2.54mm)   Number of Rows 2   Row Spacing - Mating 0.100" (2.54mm)   Mounting Type 0.100" (2.54mm)   Termination Solder   Fastening Type Push-Pull   Contact Finish - Mating Gold   Contact Finish Thickness - Mating 30µin (0.76µm)   Insulation Color Blue   Insulation Height 0.335" (8.51mm)   Contact Length - Post 0.118" (3.00mm)	Contact Type	Female Socket
Number of Positions Loaded10Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlueInsulation ColorSols" (8.51mm)Contact Length - Post0.118" (3.00mm)Contact Length - Post-	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlueInsulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Number of Positions	24
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)	Number of Positions Loaded	10
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Fastening Type	Push-Pull
Insulation ColorBlueInsulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Contact Finish - Mating	Gold
Insulation Height0.335" (8.51mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post0.118" (3.00mm)Operating Temperature-	Insulation Color	Blue
Operating Temperature -	Insulation Height	0.335" (8.51mm)
	Contact Length - Post	0.118" (3.00mm)
Material Flammability Rating III 94 V-0	Operating Temperature	-
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### 91625-317LF Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 91625-317LF, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com