

9290-05-20 Information

Heisener.com

Part Number 9290-05-20 Manufacturer Coto Technology

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY RF SPST 500MA 5V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9290-05-20 Specifications

Manufacturer Part Number 9290-05-20 Manufacturer Coto Technology Category Relays Signal Relays, Up to 2 Amps Package - Series 9290 Relay Type RF Coil Type Non Latching Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms Release Time 0.1ms		
Category Relays Signal Relays, Up to 2 Amps Package - Series 9290 Relay Type RF Coil Type Non Latching Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Manufacturer Part Number	9290-05-20
Package - Series 9290 Relay Type RF Coil Type Non Latching Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Manufacturer	Coto Technology
Package - Series 9290 Relay Type RF Coil Type Non Latching Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Category	Relays
Series 9290 Relay Type RF Coil Type Non Latching Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms		Signal Relays, Up to 2 Amps
Relay Type RF Coil Type Non Latching Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Package	-
Coil TypeNon LatchingCoil Current31.3mACoil Voltage5VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)500mASwitching Voltage200VAC, 200VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)0.4 VDCOperate Time0.4ms	Series	9290
Coil Current 31.3mA Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Relay Type	RF
Coil Voltage 5VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 500mA Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Coil Current	31.3mA
Contact Rating (Current) Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Coil Voltage	5VDC
Switching Voltage 200VAC, 200VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) 0.4 VDC Operate Time 0.4ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 3.75 VDC 0.4 VDC 0.4ms	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 0.4 VDC 0.4ms	Switching Voltage	200VAC, 200VDC - Max
Operate Time 0.4ms	Turn On Voltage (Max)	3.75 VDC
	Turn Off Voltage (Min)	0.4 VDC
Release Time 0.1ms	Operate Time	0.4ms
	Release Time	0.1ms
Features Magnetic Shield	Features	Magnetic Shield
Mounting Type Surface Mount	Mounting Type	Surface Mount
Termination Style J Lead	Termination Style	J Lead
Report errors?		Report errors?

9290-05-20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9290-05-20 Payment Methods



















9290-05-20 Shipping Methods













If you have any question about 9290-05-20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com