

929834-07-24

929834-07-24 Information

www.neisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



929834-07-24 Specifications

Manufacturer Part Number	929834-07-24
Manufacturer	3M
Category	Connectors, Interconnects
	Rectangular Connectors - Headers, Male Pins
Package	-
Series	929
Connector Type	Header, Breakaway
Contact Type	Male Pin
Pitch - Mating	0.100" (2.54mm)
Style	Board to Board
Shrouding	Unshrouded
Number of Positions	24
Number of Positions Loaded	All
Number of Rows	1
Row Spacing - Mating	-
Mounting Type	Through Hole
Termination	Solder
Fastening Type	Push-Pull
Contact Length - Mating	0.235" (5.97mm)
Contact Length - Post	0.910" (23.11mm)
Overall Contact Length	1.245" (31.62mm)
Insulation Height	0.100" (2.54mm)
Contact Shape	Square
Contact Finish - Mating	Tin-Lead

Contact Finish Thickness - Mating	100µin (2.54µm)	
Contact Finish - Post	-	
Contact Material	Copper Alloy	
Insulation Material	Polybutylene Terephthalate (PBT), Polyester, Glass Filled	
Features	-	
Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$	
Ingress Protection	-	
Material Flammability Rating	UL94 V-0	
Insulation Color	Black	
		Report errors?

929834-07-24 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

929834-07-24 Payment Methods



If you have any question about 929834-07-24, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com