



929850-01-13-RA Information

Part Number 929850-01-13-RA

Manufacturer 3M

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RECEPT .100 SNGL STR 13POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









929850-01-13-RA Specifications

Manufacturer Part Number 929850-01-13-RA Manufacturer 3M Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	929850-01-13-RA
Package-Series929Connector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions13Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Manufacturer	3M
Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects
Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Package	-
Contact Type Forked Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Series	929
Style Board to Board Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Connector Type	Receptacle
Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Style	Board to Board
Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Number of Positions	13
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $10\mu in (0.25\mu m)$ Insulation ColorBlackInsulation Height $0.325" (8.25mm)$ Contact Length - Post $0.125" (3.18mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μ in $(0.25\mu$ m) Insulation Color Black Insulation Height $0.325''$ $(8.25mm)$ Contact Length - Post $0.125''$ $(3.18mm)$ Operating Temperature -40° C $\sim 105^{\circ}$ C	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μ in $(0.25\mu$ m) Insulation Color Black Insulation Height 0.325 " $(8.25$ mm) Contact Length - Post 0.125 " $(3.18$ mm) Operating Temperature -40 °C ~ 105 °C	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating $10\mu in (0.25\mu m)$ Insulation Color Black Insulation Height $0.325'' (8.25mm)$ Contact Length - Post $0.125'' (3.18mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Termination	Solder
Contact Finish Thickness - Mating 10μ in $(0.25\mu$ m) Insulation Color Black Insulation Height 0.325 " $(8.25$ mm) Contact Length - Post 0.125 " $(3.18$ mm) Operating Temperature -40 °C ~ 105 °C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.325"$ ($8.25mm$)Contact Length - Post $0.125"$ ($3.18mm$)Operating Temperature -40 °C ~ 105 °C	Contact Finish - Mating	Gold
Insulation Height $0.325"$ (8.25mm)Contact Length - Post $0.125"$ (3.18mm)Operating Temperature -40 °C ~ 105 °C	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post $0.125" (3.18mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.325" (8.25mm)
	Contact Length - Post	0.125" (3.18mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

929850-01-13-RA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

929850-01-13-RA Payment Methods



















929850-01-13-RA Shipping Methods













If you have any question about 929850-01-13-RA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com