



929975-01-29-RK Information

Part Number 929975-01-29-RK

Manufacturer 3M

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RECEPT .100 DUAL STR 58POS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









929975-01-29-RK Specifications

Manufacturer Part Number 929975-01-29-RK Manufacturer 3M Category Connectors, Interconnects Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Testening Type Through Hole Fastening Type Push-Pull Contact Finish - Mating 100µin (2.54µm) Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature 40°C ~ 105°C Material Flammability Rating UL94 V-0				
Category Connectors, Interconnects Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating 100μin (2.54μm) Contact Finish Thickness - Mating 100μin (2.54μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	929975-01-29-RK		
Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Manufacturer	3M		
Package - Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μin (2.54μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects		
Series 929 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μin (2.54μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions58Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Package	-		
Contact TypeForkedStyleBoard to BoardNumber of Positions58Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Series	929		
Style Board to Board Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Connector Type	Receptacle		
Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μin (2.54μm) Insulation Color Black Insulation Height 0.325" (8.25mm) Contact Length - Post 0.125" (3.18mm) Operating Temperature -40°C ~ 105°C	Contact Type	Forked		
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.325" (8.25mm)Contact Length - Post0.125" (3.18mm)Operating Temperature-40°C ~ 105°C	Style	Board to Board		
Pitch - Mating 0.100° (2.54mm)Number of Rows2Row Spacing - Mating 0.100° (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating 100μ in (2.54 μ m)Insulation ColorBlackInsulation Height 0.325° (8.25mm)Contact Length - Post 0.125° (3.18mm)Operating Temperature -40° C ~ 105° C	Number of Positions	58		
Number of Rows2Row Spacing - Mating $0.100"$ (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating 100μ in (2.54 μ m)Insulation ColorBlackInsulation Height $0.325"$ (8.25mm)Contact Length - Post $0.125"$ (3.18mm)Operating Temperature -40° C ~ 105° C	Number of Positions Loaded	All		
Row Spacing - Mating $0.100" (2.54mm)$ Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μ in $(2.54\mu$ m) Insulation Color Black Insulation Height $0.325" (8.25mm)$ Contact Length - Post $0.125" (3.18mm)$ Operating Temperature -40° C $\sim 105^{\circ}$ C	Pitch - Mating	0.100" (2.54mm)		
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating 100μ in (2.54μm)Insulation ColorBlackInsulation Height 0.325 " (8.25mm)Contact Length - Post 0.125 " (3.18mm)Operating Temperature -40 °C ~ 105 °C	Number of Rows	2		
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μ in $(2.54\mu$ m) Insulation Color Black Insulation Height $0.325''$ $(8.25mm)$ Contact Length - Post $0.125''$ $(3.18mm)$ Operating Temperature -40° C $\sim 105^{\circ}$ C	Row Spacing - Mating	0.100" (2.54mm)		
Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μ in $(2.54\mu$ m) Insulation Color Black Insulation Height 0.325 " $(8.25$ mm) Contact Length - Post 0.125 " $(3.18$ mm) Operating Temperature -40 °C ~ 105 °C	Mounting Type	Through Hole		
Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μ in $(2.54\mu$ m) Insulation Color Black Insulation Height 0.325 " (8.25mm) Contact Length - Post 0.125 " (3.18mm) Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Termination	Solder		
Contact Finish Thickness - Mating 100μ in (2.54 μ m) Insulation Color Black Insulation Height 0.325 " (8.25mm) Contact Length - Post 0.125 " (3.18mm) Operating Temperature -40 °C ~ 105 °C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height $0.325"$ ($8.25mm$)Contact Length - Post $0.125"$ ($3.18mm$)Operating Temperature -40 °C ~ 105 °C	Contact Finish - Mating	Tin		
Insulation Height $0.325" (8.25mm)$ Contact Length - Post $0.125" (3.18mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	100μin (2.54μm)		
Contact Length - Post 0.125 " (3.18mm) Operating Temperature -40 °C ~ 105 °C	Insulation Color	Black		
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.325" (8.25mm)		
	Contact Length - Post	0.125" (3.18mm)		
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C		
	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

929975-01-29-RK Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

929975-01-29-RK Payment Methods



















929975-01-29-RK Shipping Methods













If you have any question about 929975-01-29-RK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com