



94SVP476X06R3B6 Information



For Reference Only

Part Number94SVP476X06R3B6ManufacturerVishay SpragueCategoryCapacitors

Aluminum - Polymer Capacitors

Description CAP ALUM POLY 47UF 20% 6.3V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









94SVP476X06R3B6 Specifications

Manufacturer Part Number 94SVP476X06R3B6 Manufacturer Vishay Sprague Category Capacitors Aluminum - Polymer Capacitors Package Radial, Can - SMD Series 94SVP Type Polymer Capacitance 47µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" Lx 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	•	
Category Capacitors Aluminum - Polymer Capacitors Package Radial, Can - SMD Scries 94SVP Type Polymer Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	94SVP476X06R3B6
Aluminum - Polymer Capacitors Package Radial, Can - SMD Series 94SVP Type Polymer Capacitance 47µF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.206" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Package / Case Radial, Can - SMD	Manufacturer	Vishay Sprague
Package Radial, Can - SMD Series 94SVP Type Polymer Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series 94SVP Type Polymer Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum - Polymer Capacitors
Type Polymer Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Package	Radial, Can - SMD
Capacitance 47μF Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	94SVP
Tolerance ±20% Voltage - Rated 6.3V ESR (Equivalent Series Resistance) 90 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Туре	Polymer
Voltage - Rated ESR (Equivalent Series Resistance) Derating Temp. Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing Size / Dimension O.197" Dia (5.00mm) Height - Seated (Max) Surface Mount Land Size O.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency -Ripple Current - High Frequency 1.06A @ 100kHz Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Package / Case Radial, Can - SMD	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 1.06A @ 100kHz Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Package / Case 1000 Hrs @ 105°C General Purpose - 1.06A @ 100kHz 1.	Voltage - Rated	6.3V
Operating Temperature Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case General Purpose - 1.06A @ 100kHz 1.06A @ 1	ESR (Equivalent Series Resistance)	90 mOhm
Applications Ripple Current - Low Frequency - Ripple Current - High Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lifetime @ Temp.	1000 Hrs @ 105°C
Ripple Current - Low Frequency 1.06A @ 100kHz Impedance - Lead Spacing - Current - Dia (5.00mm) Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Operating Temperature	-55°C ~ 105°C
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Package / Case 1.06A @ 100kHz 1.06A	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 0.197" Dia (5.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	1.06A @ 100kHz
Size / Dimension0.197" Dia (5.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size0.209" L x 0.209" W (5.30mm x 5.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-
Height - Seated (Max) Surface Mount Land Size 0.236" (6.00mm) 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.209" L x 0.209" W (5.30mm x 5.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.197" Dia (5.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.236" (6.00mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.209" L x 0.209" W (5.30mm x 5.30mm)
-	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

94SVP476X06R3B6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

94SVP476X06R3B6 Payment Methods



















94SVP476X06R3B6 Shipping Methods













If you have any question about 94SVP476X06R3B6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com