



95C06A4GWT Information

Heisener com

Part Number95C06A4GWTManufacturerGrayhill Inc.CategorySwitches

Tactile Switches

Description SWITCH TACTILE SPST-NO 0.05A 12V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









95C06A4GWT Specifications

Manufacturer Part Number 95C06A4GWT Manufacturer Grayhill Inc. Category Switches Package - Series 95C Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.29mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Tactile Feedback		
Category Switches Package - Series 95C Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.29mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Tactile Feedback	Manufacturer Part Number	95C06A4GWT
Package - Series 95C Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.29mm Actuator Length, Right Angle - Contact Ration Style Gull Wing Outline 6.20mm x 6.20mm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) - Coperating Force 260gf Ingress Protection - Features Tackles Surface Mount - Communicated Surface Mount - Communicated Surface Mount - Communicated Surface Mount - Communicated Surface Mount - Coperating Force 260gf Ingress Protection - Tactile Feedback	Manufacturer	Grayhill Inc.
Package-Series95CCircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical4.29mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesTactile Feedback	Category	Switches
Series 95C Circuit SPST-NO Switch Function Off-Mom Contact Rating @ Voltage 0.05A @ 12VDC Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical 4.29mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Tactile Feedback		Tactile Switches
CircuitSPST-NOSwitch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical4.29mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesTactile Feedback	Package	-
Switch FunctionOff-MomContact Rating @ Voltage0.05A @ 12VDCActuator TypeStandardMounting TypeSurface MountActuator Height off PCB, Vertical4.29mmActuator Length, Right Angle-Actuator OrientationTop ActuatedTermination StyleGull WingOutline6.20mm x 6.20mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesTactile Feedback	Series	95C
Contact Rating @ Voltage Actuator Type Standard Mounting Type Surface Mount Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Outline G.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features O.05A @ 12VDC Standard Standard Standard Standard Standard Standard Standard Standard Actuator Surface Mount A.29mm A.29mm A.29mm A.20mm A.2	Circuit	SPST-NO
Actuator Type Surface Mount Actuator Height off PCB, Vertical 4.29mm Actuator Length, Right Angle - Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Tactile Feedback	Switch Function	Off-Mom
Mounting Type Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Surface Mount 4.29mm Actuator Mount 4.29mm Actuated Gull Wing Gull Wing Gull Wing 6.20mm x 6.20mm Non-Illuminated - 260gf Tactile Feedback	Contact Rating @ Voltage	0.05A @ 12VDC
Actuator Height off PCB, Vertical Actuator Length, Right Angle Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features 4.29mm 4.29	Actuator Type	Standard
Actuator Length, Right Angle Actuator Orientation Top Actuated Gull Wing Outline 6.20mm x 6.20mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features - Tactile Feedback	Mounting Type	Surface Mount
Actuator Orientation Top Actuated Termination Style Gull Wing Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Tactile Feedback	Actuator Height off PCB, Vertical	4.29mm
Termination Style Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Operating Force Ingress Protection Features Tactile Feedback	Actuator Length, Right Angle	-
Outline 6.20mm x 6.20mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Operating Force 260gf Ingress Protection - Features Tactile Feedback	Actuator Orientation	Top Actuated
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesTactile Feedback	Termination Style	Gull Wing
Illumination Type, Color-Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesTactile Feedback	Outline	6.20mm x 6.20mm
Illumination Voltage (Nominal)-Operating Force260gfIngress Protection-FeaturesTactile Feedback	Illumination	Non-Illuminated
Operating Force260gfIngress Protection-FeaturesTactile Feedback	Illumination Type, Color	-
Ingress Protection - Tactile Feedback	Illumination Voltage (Nominal)	-
Features Tactile Feedback	Operating Force	260gf
	Ingress Protection	-
Report errors?	Features	Tactile Feedback
		Report errors?

95C06A4GWT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

95C06A4GWT Payment Methods





















95C06A4GWT Shipping Methods













If you have any question about 95C06A4GWT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com