

960268-6303-AR

960268-6303-AR Information

Heisener.com	Part Number Manufacturer Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description Package	CONN SOCKET DUAL VERT 68POS GOLD	
	8	For the pricing/inventory/lead time, please contact	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



960268-6303-AR Specifications

Manufacturer Part Number960268-6303-ARManufacturer3MCategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-Series960Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mouning TypeThrough HoleFrastening TypeQuid AllContact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Finish Thicknes - MatingGoldContact Finish Thicknes - MatingFlashContact Finish Thicknes - MatingFlashContact Funish Thicknes - MatingGoldContact Finish Thicknes - MatingFlashContact Funish Thicknes - MatingFlashContact Lenoth - Post0.138" (8.51mm)		
CategoryConnectors, InterconnectsPackage-Series960Connector TypeReceptacle SectorContact TypeReceptacle SectorStyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypeGoldContact Finish - MatingGoldFastening TypeBashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Manufacturer Part Number	960268-6303-AR
Indext Connectors - Headers, Receptacles, Female SocketsPackage-Series960Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions68Number of Positions Loaded1010° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Number of Rows0.100° (2.54mm)Number of Rows0.100° (2.54mm)Number of Rows0.100° (2.54mm)Number of Rows0.100° (2.54mm)ForninationSolderForninationSolderContact Finish - MatingOldContact Finish - MatingGoldContact Finish - MatingFashInsulation ColorHackInsulation FinishSolas" (3.51mm)	Manufacturer	3M
Package-Series960Conector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingSolderContact Finish - MatingGoldState Times - MatingGoldState Times - MatingBiackInsulation ColorJ.33S" (8.51mm)	Category	Connectors, Interconnects
Series960Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - MatingFashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQui AllContact Finish - MatingGoldContact Finish - MatingBlackInsulation ColorBlackInsulation Height0.335" (8.51mm)	Series	960
StyleBoard to BoardNumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.335" (8.51mm)	Connector Type	Receptacle
Yumber of Positions68Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.335" (8.51mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Number of Positions	68
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Termination	Solder
Contact Finish Thickness - MatingFlashInsulation ColorBlackInsulation Height0.335" (8.51mm)	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.335" (8.51mm)	Contact Finish - Mating	Gold
Insulation Height 0.335" (8.51mm)	Contact Finish Thickness - Mating	Flash
	Insulation Color	Black
Contact Length - Post 0 138" (3 50mm)	Insulation Height	0.335" (8.51mm)
contact Dengui Tost (150 (150 mil))	Contact Length - Post	0.138" (3.50mm)
Operating Temperature $-25^{\circ}C \sim 105^{\circ}C$	Operating Temperature	-25°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

960268-6303-AR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

960268-6303-AR Payment Methods



If you have any question about 960268-6303-AR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com