



96PSA-A84W12V1 Information



For Reference Only

Part Number 96PSA-A84W12V1 Manufacturer Advantech Corp

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 84W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









96PSA-A84W12V1 Specifications

Manufacturer Part Number 96PSA-A84W12V1 Manufacturer Advantech Corp Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Manufacturer Part Number	96PSA-A84W12V1	
AC DC Desktop, Wall Adapters Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension \$ 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Manufacturer	Advantech Corp	
Package - Series - Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series-Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7APower (Watts)84WNo Load Power Consumption210mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)		AC DC Desktop, Wall Adapters	
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Package	-	
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Series	-	
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Region Utilized	International	
Voltage - Input90 ~ 264 VACVoltage - Output12VCurrent - Output (Max)7APower (Watts)84WNo Load Power Consumption210mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VIOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mmSize / Dimension6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Form	Desktop (Class I)	
Voltage - Output (Max) 7A Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Input Type	Cord (Sold Separately)	
Current - Output (Max) Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Voltage - Input	90 ~ 264 VAC	
Power (Watts) 84W No Load Power Consumption 210mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Voltage - Output	12V	
No Load Power Consumption 210mW (Max) Polarization -	Current - Output (Max)	7A	
Polarization - Applications ITE (Commercial) Efficiency Level VI Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Power (Watts)	84W	
Applications ITE (Commercial) Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $6.30^{\circ}\text{L} \times 2.28^{\circ}\text{W} \times 1.27^{\circ}\text{H} (160.0\text{mm} \times 58.0\text{mm} \times 32.3\text{mm})$	No Load Power Consumption	210mW (Max)	
Efficiency Level VI Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $6.30^{\circ}\text{L} \times 2.28^{\circ}\text{W} \times 1.27^{\circ}\text{H} (160.0\text{mm} \times 58.0\text{mm} \times 32.3\text{mm})$	Polarization	-	
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension $6.30^{\circ}\text{L} \times 2.28^{\circ}\text{W} \times 1.27^{\circ}\text{H} (160.0\text{mm} \times 58.0\text{mm} \times 32.3\text{mm})$	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Efficiency	Level VI	
Size / Dimension 6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	Operating Temperature	0°C ~ 40°C	
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 11.0mm	
Report errors?	Size / Dimension	6.30" L x 2.28" W x 1.27" H (160.0mm x 58.0mm x 32.3mm)	
		Report e	errors?

96PSA-A84W12V1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

96PSA-A84W12V1 Payment Methods



















96PSA-A84W12V1 Shipping Methods













If you have any question about 96PSA-A84W12V1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com