

# 97-3106A-14S-5S(946)

## 97-3106A-14S-5S(946) Information

|                            |              | 97-3106A-14S-5S(946)  |                 |
|----------------------------|--------------|---|-----------------|
|                            | Manufacturer | Amphenol Industrial Operations  |                 |
| elsener.com                | Category     | Connectors, Interconnects<br>Circular Connectors                          |                 |
| Concernation of the second | Description  | CONN PLUG 5POS W/SOCKETS  | 532439          |
|                            | Package      | -   |                 |
|                            |              | For the pricing/inventory/lead time, please contact                       | E1264-42779     |
| For Reference Only         |              | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com | Request a Quote |

E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 97-3106A-14S-5S(946) Specifications

| Manufacturer Part Number97.3106A-14S-5S(946)ManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-Series97Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A  |                          |                                |
|---|--------------------------|--------------------------------|
| CategoryConnectors, Interconnects<br>Circular ConnectorsPackage-Series97Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientation.Shell Material, FinishAluminum, Zinc Plated, BlackContact Finish-Shell Material, FinishSilverFeatures-Voltage - Rated100VAC, 250VDCCurrent Rating13A  | Manufacturer Part Number | 97-3106A-14S-5S(946)           |
| Initial ConnectorsPackage-Series97Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated20VAC, 250VDCCurrent Rating13A   | Manufacturer             | Amphenol Industrial Operations |
| Package-Series97Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated20VAC, 250VDCCurrent Rating13A   | Category                 | Connectors, Interconnects      |
| Series97Connector TypePlug, Female SocketsNumber of Positions5Shell Size - InsertI4S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishSilverContact FinishSilverFastening-Fortures3ilverFastening3ilverFurtures3ilverFurtures3ilverFortures3ilverFurture |                          | Circular Connectors            |
| Connector TypePlug, Female SocketsNumber of Positions5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishSilverFoaturesSilverFoatures200VAC, 250VDCFurent Rating13A  | Package                  | -                              |
| Number of Positions5Number of Positions14S-5Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact Finish-Features-Voltage - Rated200VAC, 250VDCCurrent Rating13A  | Series                   | 97                             |
| Shell Size - Insert14S-5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact Finish-Features-Voltage - Rated200VAC, 250VDCCurrent Rating13A  | Connector Type           | Plug, Female Sockets           |
| Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCGurrent Rating13A  | Number of Positions      | 5                              |
| Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCKurent Rating13A   | Shell Size - Insert      | 14S-5                          |
| TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A  | Shell Size, MIL          | -                              |
| Fastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A   | Mounting Type            | Free Hanging (In-Line)         |
| OrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A   | Termination              | Solder Cup                     |
| Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A  | Fastening Type           | Threaded                       |
| Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A   | Orientation              | N (Normal)                     |
| Contact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A   | Ingress Protection       | -                              |
| Features-Voltage - Rated200VAC, 250VDCCurrent Rating13A   | Shell Material, Finish   | Aluminum, Zinc Plated, Black   |
| Voltage - Rated200VAC, 250VDCCurrent Rating13A  | Contact Finish           | Silver                         |
| Current Rating 13A  | Features                 | -                              |
|   | Voltage - Rated          | 200VAC, 250VDC                 |
| Report errors?  | Current Rating           | 13A                            |
|   |                          | Report errors?                 |

#### 97-3106A-14S-5S(946) Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 97-3106A-14S-5S(946) Payment Methods



### 97-3106A-14S-5S(946) Shipping Methods



If you have any question about 97-3106A-14S-5S(946), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com