

97-3106A-24-28S(946)

97-3106A-24-28S(946) Information





Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



97-3106A-24-28S(946) Specifications

Manufacturer Part Number 97.3106A-24-28S(946) Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series 97 Connector Type Plug, Female Sockets Number of Positions 24-28 Shell Size - Insert 24-28 Mounting Type Free Hanging (In-Line) Termination Solder Cup Agrees Protection - Orientation N(Normal) Ingress Protection - Shell Material, Finish Aluminum, Zinc Plated, Black Contact Finish Silver Features - Voltage - Rated 200VAC, 250VDC Current Rating I3A		
CategoryConnectors, Interconnects Circular ConnectorsPackage-Series97Connector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact Finish-Yoltage - Rated200VAC, 250VDCCurrent Rating13A	Manufacturer Part Number	97-3106A-24-28S(946)
Initial ConnectorsPackage-Series97Connector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated20VAC, 250VDCCurrent Rating13A	Manufacturer	Amphenol Industrial Operations
Package-Series97Connector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated20VAC, 250VDCCurrent Rating13A	Category	Connectors, Interconnects
Series97Connector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishSilverContact FinishSilverFeatures-Voltage - Rated13A		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions24Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishSilverContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCKurent Rating13A	Package	-
Number of Positions24Number of Positions24-28Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact Finish-Features-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Series	97
Shell Size - Insert24-28Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact Finish-Features-Voltage - Rated200VAC, 250VDCGurrent Rating13A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN(Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent RatingIa	Number of Positions	24
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedForientationN(Normal)Orientation-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCKurent Rating13A	Shell Size - Insert	24-28
TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Shell Size, MIL	-
Fastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Mounting Type	Free Hanging (In-Line)
OrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Termination	Solder Cup
Ingress Protection-Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Fastening Type	Threaded
Shell Material, FinishAluminum, Zinc Plated, BlackContact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Orientation	N (Normal)
Contact FinishSilverFeatures-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Ingress Protection	-
Features-Voltage - Rated200VAC, 250VDCCurrent Rating13A	Shell Material, Finish	Aluminum, Zinc Plated, Black
Voltage - Rated200VAC, 250VDCCurrent Rating13A	Contact Finish	Silver
Current Rating 13A	Features	-
-	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	13A
		Report errors?

E-mail: salesdept@heisener.com

97-3106A-24-28S(946) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

97-3106A-24-28S(946) Payment Methods



97-3106A-24-28S(946) Shipping Methods



If you have any question about 97-3106A-24-28S(946), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com