

9919371212 Information



For Reference Only

Part Number 9919371212 Manufacturer Weidmuller

Category Power Supplies - External/Internal (Off-Board)

DC DC Converters

Description CONV DC-DC 12V IN 12V OUT @3A

Package Modul

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









9919371212 Specifications

Manufacturer Part Number 9919371212 Manufacturer Weidmuller Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series CP-DCDC 50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	•	
Category Power Supplies - External/Internal (Off-Board) DC DC Converters Package Module Series CP-DCDC 50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Manufacturer Part Number	9919371212
Package Module Series CP-DCDC 50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Manufacturer	Weidmuller
Package Module Series CP-DCDC 50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series CP-DCDC 50W Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)		DC DC Converters
Type Isolated Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Package	Module
Voltage - Input (Min) 9V Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Series	CP-DCDC 50W
Voltage - Input (Max) 16V Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Туре	Isolated
Number of Outputs 1 Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 3A Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Voltage - Input (Min)	9V
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Operating Temperature Efficiency Mounting Type DIN Rail Package / Case Size / Dimension 12V - 12V 12V 12V 12V 12V 12V 1	Voltage - Input (Max)	16V
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension - - - - - - - - - - - - -	Number of Outputs	1
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension - Output (Max) - Current - Output (Max) 3A - Current - Output (Max) 50W - Current - Output (Max) 50W - Current - Output (Max) 50W - Output (Max) - Output (Max	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Applications Operating Temperature Efficiency Mounting Type DIN Rail Package / Case Module Size / Dimension - Output (Max) 3A - Output (Max) 50W - Output (Max) - Output (Max) 50W - Output (Max) - Output (Max) 50W - Output (Max) - Output (Max)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 3A 50W ITE (Commercial) -10°C ~ 50°C But (Commercial) -10°C ~ 50°C -10	Voltage - Output 3	-
Power (Watts) 50W Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Voltage - Output 4	-
Applications ITE (Commercial) Operating Temperature -10°C ~ 50°C Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Current - Output (Max)	3A
$ \begin{array}{llllllllllllllllllllllllllllllllllll$	Power (Watts)	50W
Efficiency 80% Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Applications	ITE (Commercial)
Mounting Type DIN Rail Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Operating Temperature	-10°C ~ 50°C
Package / Case Module Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Efficiency	80%
Size / Dimension 5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)	Mounting Type	DIN Rail
	Package / Case	
Report errors?	Size / Dimension	5.16" L x 2.24" W x 3.86" H (131.0mm x 57.0mm x 98.0mm)
		Report errors?

9919371212 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

9919371212 Payment Methods



















9919371212 Shipping Methods













If you have any question about 9919371212, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com