

A011-D-V-500 Information



For Reference Only

Part Number A011-D-V-500 Manufacturer LEDdynamics Inc.

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DVR CC BUCK-BOOST 48V 500MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A011-D-V-500 Specifications

Manufacturer Part Number A011-D-V-500 Manufacturer LEDdynamics Inc. Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series FlexBlock? A011 Type Constant Current Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series FlexBlock? A011 Type Constant Current Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Manufacturer Part Number	A011-D-V-500	
Package - Series FlexBlock? A011 Type Constant Current Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Manufacturer	LEDdynamics Inc.	
Package - Series FlexBlock? A011 Type Constant Current Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series FlexBlock? A011 Type Constant Current Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)		LED Drivers	
Type Constant Current Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Package	-	
Topology Buck-Boost Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Output (Max) 32V Voltage - Output (Max) 500mA Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Series	FlexBlock? A011	
Number of Outputs 1 Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Туре	Constant Current	
Voltage - Input (Min) 10V Voltage - Input (Max) 32V Voltage - Output 48V (Max) Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Topology	Buck-Boost	
Voltage - Input (Max)32VVoltage - Output48V (Max)Current - Output (Max)500mAPower (Watts)24WVoltage - Isolation-DimmingAnalogFeaturesSCPRatings-Operating Temperature-Efficiency90%Termination StyleWire LeadsSize / Dimension2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Number of Outputs	1	
Voltage - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Voltage - Input (Min)	10V	
Current - Output (Max) 500mA Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 24W Current - Output (Max) 500mA	Voltage - Input (Max)	32V	
Power (Watts) 24W Voltage - Isolation - Dimming Analog Features SCP Ratings - Operating Temperature Efficiency 90% Termination Style Size / Dimension 24W Analog - Analog Analog Analog Analog BCP Analog Analog Analog BCP Analog BCP Analog Analog BCP Analog BCP Analog Analog Analog BCP Analog Analog BCP Analog Analog BCP Analog BCP Analog BCP Analog Analog BCP Analog BCP Analog Analog BCP BCP Analog BCP BCP Analog BCP BCP BCP BCP BCP BCP BCP BC	Voltage - Output	48V (Max)	
Voltage - Isolation-DimmingAnalogFeaturesSCPRatings-Operating Temperature-Efficiency90%Termination StyleWire LeadsSize / Dimension2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Current - Output (Max)	500mA	
Dimming Analog Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Power (Watts)	24W	
Features SCP Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Voltage - Isolation	-	
Ratings - Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Dimming	Analog	
Operating Temperature - Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Features	SCP	
Efficiency 90% Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Ratings	-	
Termination Style Wire Leads Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Operating Temperature	-	
Size / Dimension 2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	Efficiency	90%	
	Termination Style	Wire Leads	
Report errors	Size / Dimension	2.00" L x 1.20" W x 0.38" H (50.8mm x 30.5mm x 9.5mm)	
· · · · · · · · · · · · · · · · · · ·		Report error	ors?

A011-D-V-500 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A011-D-V-500 Payment Methods



















A011-D-V-500 Shipping Methods













If you have any question about A011-D-V-500, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com