

A181K15X7RF5UAA

A181K15X7RF5UAA Information



For Reference Only

Part Number A181K15X7RF5UAA

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 180PF 50V X7R AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A181K15X7RF5UAA Specifications

Manufacturer Part Number A181K15X7RF5UAA Manufacturer Vishay BC Components Category Capacitors Package Axial Series A Capacitance 180pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style -		
Category Capacitors Package Axial Series A Capacitance 180pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	A181K15X7RF5UAA
Package Axial Series A Capacitance 180pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	Vishay BC Components
Package Axial Series A Capacitance 180pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series A Capacitance 180pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 180pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Series	A
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.098" Dia x 0.150" L (2.50mm x 3.80mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	180pF
Temperature Coefficient Ayr Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - X7R Agriculture Rate - Axial - 1. 1. 1. 1. 1. 1. 1. 1. 1.	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.098" Dia x 0.150" L (2.50mm x 3.80mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	50V
Features Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Ratings	-
Mounting Type Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Through Hole Axial 0.098" Dia x 0.150" L (2.50mm x 3.80mm) - Case (Max) - Case (Max)	Applications	General Purpose
Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.098" Dia x 0.150" L (2.50mm x 3.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

A181K15X7RF5UAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A181K15X7RF5UAA Payment Methods



















A181K15X7RF5UAA Shipping Methods













If you have any question about A181K15X7RF5UAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com