

A2200-A Information



For Reference Only

Part Number A2200-A

Manufacturer Maestro Wireless Solutions

Category RF/IF and RFID

RF Receivers

Description MODULE GPS SIRFSTARIV

Package Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A2200-A Specifications

Manufacturer A2200-A Manufacturer Maestro Wireless Solutions Category RF/IF and RFID RF Receivers RF Receivers Package Module Series SiRFstarIV? Frequency 1.575GHz Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply 3.3V Operating Temperature -40°C ~ 85°C Package / Case Module		
Category RF/IF and RFID RF Receivers Package Module Series SiRFstarIV? Frequency 1.575GHz Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply 3.3V Operating Temperature -40°C ~ 85°C	Manufacturer Part Number	A2200-A
Package Module Series SiRFstarIV? Frequency 1.575GHz Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply Operating Temperature -40°C ~ 85°C	Manufacturer	Maestro Wireless Solutions
Package Series SiRFstarIV? Frequency 1.575GHz Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector Features Voltage - Supply Operating Temperature Module SiRFstarIV? 69mA 69s 69s 69mA 591 - 40°C ~ 85°C	Category	RF/IF and RFID
Series SiRFstarIV? Frequency 1.575GHz Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply 3.3V Operating Temperature -40°C ~ 85°C		RF Receivers
Frequency 1.575GHz Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply 3.3V Operating Temperature -40°C ~ 85°C	Package	Module
Sensitivity -163dBm Data Rate (Max) 4.8Mbps Modulation or Protocol GPS Applications General Purpose Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply 3.3V Operating Temperature -40°C ~ 85°C	Series	SiRFstarIV?
Data Rate (Max)4.8MbpsModulation or ProtocolGPSApplicationsGeneral PurposeCurrent - Receiving69mAData InterfaceSPIMemory Size-Antenna Connector-Features-Voltage - Supply3.3VOperating Temperature-40°C ~ 85°C	Frequency	1.575GHz
Modulation or ProtocolGPSApplicationsGeneral PurposeCurrent - Receiving69mAData InterfaceSPIMemory Size-Antenna Connector-Features-Voltage - Supply3.3VOperating Temperature-40°C ~ 85°C	Sensitivity	-163dBm
Applications Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector Features Voltage - Supply Operating Temperature General Purpose 69mA - SPI - 3.3V -40°C ~ 85°C	Data Rate (Max)	4.8Mbps
Current - Receiving 69mA Data Interface SPI Memory Size - Antenna Connector - Features - Voltage - Supply 3.3V Operating Temperature -40°C ~ 85°C	Modulation or Protocol	GPS
Data InterfaceSPIMemory Size-Antenna Connector-Features-Voltage - Supply $3.3V$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Applications	General Purpose
$\begin{array}{cccccccccccccccccccccccccccccccccccc$	Current - Receiving	69mA
Antenna Connector Features Voltage - Supply $3.3V$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Data Interface	SPI
Features - Voltage - Supply 3.3V Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Memory Size	-
Voltage - Supply $3.3V$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Antenna Connector	-
Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Features	-
	Voltage - Supply	3.3V
Package / Case Module	Operating Temperature	-40°C ~ 85°C
	Package / Case	Module
Supplier Device Package Module	Supplier Device Package	Module
Report errors?		Report errors?

A2200-A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A2200-A Payment Methods



















A2200-A Shipping Methods













If you have any question about A2200-A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com