



A223K12KZG Information

Heisener.com

For Reference Only

Part Number A223K12KZG
Manufacturer Electroswitch
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A223K12KZG Specifications

Manufacturer Part Number A223K12KZG Manufacturer Electroswitch Category Switches Package - Series A Circuit DPDT Switch Function On-On Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesACircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length15.47mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-	Manufacturer Part Number	A223K12KZG
Package Series A Circuit DPDT Switch Function On-On Current Rating 6A (AC/DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Locking Lever Actuator Length Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection - Toggle Switches - A - A - A - A - A - A - A - A - Bushing Thread I - Ingress Protection - Ingress Protection - A - A - A - A - A - A - A - A - A - A - A - A - A - A - A - A - A - A - A - Bushing Thread I - A - Ingress Protection - - A -	Manufacturer	Electroswitch
Package - Series A Circuit DPDT Switch Function On-On Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection -	Category	Switches
SeriesACircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length15.47mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeLocking LeverActuator Length15.47mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-	Package	-
Switch Function Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Sushing Thread Ingress Protection On-On 6A (AC/DC) 125V ACV 125V AND 125V ACV 126V Panel Mount 15.47mm Non-Illuminated 15.47mm Non-Illuminated 15.47mm Solder Leg Panel Mount - 14-40 Ingress Protection - 14-40	Series	A
Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection -	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Locking Lever Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection 125V 28V Actuator Length Locking Lever Locking Lever Actuator Length 15.47mm Non-Illuminated - Sonder Lug Panel Mount 1/4-40 Ingress Protection -	Switch Function	On-On
Voltage Rating - DC Actuator Type Locking Lever 15.47mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection 28V Locking Lever Locking Lever 15.47mm Non-Illuminated Panel Mount Solder Lug Panel Mount 1/4-40 Ingress Protection -	Current Rating	6A (AC/DC)
Actuator Type Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color	Voltage Rating - AC	125V
Actuator Length 15.47mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection -	Voltage Rating - DC	28V
Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Bushing Thread 1/4-40 Ingress Protection	Actuator Type	Locking Lever
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread Ingress Protection - Illumination Type, Color - Panel Mount Solder Lug - 1/4-40 - Ingress Protection -	Actuator Length	15.47mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection -	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection -	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	-
	Bushing Thread	1/4-40
Features Epoxy Sealed Terminals	Ingress Protection	-
_L \	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

A223K12KZG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A223K12KZG Payment Methods





















A223K12KZG Shipping Methods













If you have any question about A223K12KZG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com