



A226L11YZQ Information

Heisener.com

Part Number A226L11YZQ
Manufacturer Electroswitch
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A226L11YZQ Specifications

Manufacturer Part Number A226L11YZQ Manufacturer Electroswitch Category Switches Package - Series A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 16.26mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesACircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	A226L11YZQ
Package - Series A Scries DPDT Switch Function On-Mom Current Rating On-Mom Current Rating - AC 125V Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Standard Round 16.26mm Illumination Type, Color 11lumination Type, Color 11lumination Type, Color 11lumination Type Panel Mount 11lumination Type Panel Mount 12 Solder Lug Panel Cutout Dimensions - Solder Lug Panel Cutout Dimensions - Seatures Peatures 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	Electroswitch
Package - Series A Circuit DPDT Switch Function On-Mom Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 16.26mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
SeriesACircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125 VVoltage Rating - DC28 VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-MomCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	A
Current Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length16.26mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Mom
Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features 28V Standard Round Standa	Current Rating	6A (AC/DC)
Actuator Type Standard Round Actuator Length 16.26mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features 16.26mm Non-Illuminated Panel Mount - 114-40 Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Style Solder Lug Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	16.26mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
Report circus.		Report errors?

A226L11YZQ Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A226L11YZQ Payment Methods



















A226L11YZQ Shipping Methods













If you have any question about A226L11YZQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com