



# **A232P41DZQ Information**

(A) Heisener.com

Part Number A232P41DZQ
Manufacturer Electroswitch
Category Switches

**Toggle Switches** 

**Description** SWITCH TOGGLE SP3T 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **A232P41DZQ Specifications**

Manufacturer Part Number         A232P41DZQ           Manufacturer         Electroswitch           Category         Switches           Package         -           Series         A           Circuit         SP3T           Switch Function         On-On-On           Current Rating         6A (AC/DC)           Voltage Rating - AC         125V           Voltage Rating - DC         28V           Actuator Type         Flatted           Actuator Length         6.35mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         -           Bushing Thread         1/4-40           Ingress Protection         -           Features         Jumper needed to achieve triple throw		
CategorySwitchesPackage-SeriesACircuitSP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeFlattedActuator Length6.35mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Manufacturer Part Number	A232P41DZQ
Package - Greis A A - Gircuit SP3T Switch Function On-On-On On On-On-On On On-On-On On On-On-On On On-On-On On On-On-On On On-On On On-On-On On-On-On-On On-On-On On-On-On On-On-On-On On-On-On-On On-On-On-On-On-On-On-On-On-On-On-On-On-O	Manufacturer	Electroswitch
Package - A Series A A Circuit SP3T Switch Function On-On-On Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 6.35mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Illumination Voltage (Nominal) - Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Subhing Thread 1/4-40 Ingress Protection - Jumper needed to achieve triple throw	Category	Switches
SeriesACircuitSP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeFlattedActuator Length6.35mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw		Toggle Switches
CircuitSP3TSwitch FunctionOn-On-OnCurrent Rating6A (AC/DC)Voltage Rating - AC125VVoltage Rating - DC28VActuator TypeFlattedActuator Length6.35mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Package	-
Switch Function Current Rating 6A (AC/DC) Voltage Rating - AC 125V Voltage Rating - DC 28V Actuator Type Flatted Actuator Length 6.35mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features On-On-On 6A (AC/DC) 6A	Series	A
Current Rating 6A (AC/DC)  Voltage Rating - AC 125V  Voltage Rating - DC 28V  Actuator Type Flatted  Actuator Length 6.35mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions -  Bushing Thread 1/4-40  Ingress Protection -  Features Jumper needed to achieve triple throw	Circuit	SP3T
Voltage Rating - AC  Voltage Rating - DC  28V  Actuator Type  Flatted  Actuator Length  6.35mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Bushing Thread  Ingress Protection  Features  125V  28V  Patted  6.35mm  Non-Illuminated  104-40  125V  125V  125V  126V  128V  128	Switch Function	On-On-On
Voltage Rating - DC Actuator Type Flatted Actuator Length 6.35mm  Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions - Bushing Thread Ingress Protection Features Jumper needed to achieve triple throw	Current Rating	6A (AC/DC)
Actuator Type Actuator Length 6.35mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug  Panel Cutout Dimensions - Bushing Thread Ingress Protection - Features Jumper needed to achieve triple throw	Voltage Rating - AC	125V
Actuator Length 6.35mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions -  Bushing Thread 1/4-40  Ingress Protection -  Features Jumper needed to achieve triple throw	Voltage Rating - DC	28V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions - Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Actuator Type	Flatted
Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions - Bushing Thread 1/4-40  Ingress Protection Features Jumper needed to achieve triple throw	Actuator Length	6.35mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout Dimensions-Bushing Thread1/4-40Ingress Protection-FeaturesJumper needed to achieve triple throw	Illumination	Non-Illuminated
Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions -  Bushing Thread 1/4-40  Ingress Protection -  Features Jumper needed to achieve triple throw	Illumination Type, Color	-
Termination Style Solder Lug  Panel Cutout Dimensions -  Bushing Thread 1/4-40  Ingress Protection -  Features Jumper needed to achieve triple throw	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Bushing Thread  Ingress Protection  Features  Jumper needed to achieve triple throw	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Jumper needed to achieve triple throw	Termination Style	Solder Lug
Ingress Protection - Features Jumper needed to achieve triple throw	Panel Cutout Dimensions	-
Features Jumper needed to achieve triple throw	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Jumper needed to achieve triple throw
		Report errors?

## **A232P41DZQ Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **A232P41DZQ Payment Methods**



















## **A232P41DZQ Shipping Methods**













If you have any question about A232P41DZQ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com