

A273K20X7RL5UAA

A273K20X7RL5UAA Information

Part Number A273K20X7RL5UAA Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.027UF 500V X7R AXIAL

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

www.heener.com

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A273K20X7RL5UAA Specifications

Manufacturer Part Number A273K20X7RL5UAA Manufacturer Vishay BC Components Category Capacitors Package Axial Series A Capacitance 0.027μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series A Capacitance 0.027μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	A273K20X7RL5UAA
Package Axial Series A Capacitance 0.027μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	Vishay BC Components
Package Axial Series A Capacitance 0.027μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series A Capacitance 0.027μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.027μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Series	A
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.118" Dia x 0.197" L (3.00mm x 5.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	0.027μF
Temperature Coefficient AYR Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - X7R AyR - Case - Avial - Lead Style Axial - Lead Syseing - Lead Syseing	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.118" Dia x 0.197" L (3.00mm x 5.00mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	500V
Features Ratings - Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Lead Style	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style	Applications	General Purpose
Package / Case Axial Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.118" Dia x 0.197" L (3.00mm x 5.00mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.118" Dia x 0.197" L (3.00mm x 5.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
1		Report errors?

A273K20X7RL5UAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A273K20X7RL5UAA Payment Methods



















A273K20X7RL5UAA Shipping Methods













If you have any question about A273K20X7RL5UAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com