

A330J15C0GL5TAA

A330J15C0GL5TAA Information



For Reference Only

Part Number A330J15C0GL5TAA

Manufacturer Vishay BC Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 33PF 500V C0G/NP0 AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A330J15C0GL5TAA Specifications

Manufacturer Part Number A330J15C0GL5TAA Manufacturer Vishay BC Components Category Capacitors Package Axial Series A Capacitance 33pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package Axial Series A Capacitance 33pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	A330J15C0GL5TAA
Package Axial Series A Capacitance 33pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	Vishay BC Components
PackageAxialSeriesACapacitance33pFTolerance±5%Voltage - Rated500VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.098" Dia x 0.150" L (2.50mm x 3.80mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Category	Capacitors
Series A Capacitance 33pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 33pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±5% Voltage - Rated 500V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Series	A
Voltage - Rated500VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.098" Dia x 0.150" L (2.50mm x 3.80mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	33pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - COG, NP0	Tolerance	±5%
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Voltage - Rated	500V
Features - General Purpose - General Purpose - Through Hole - Through Hole - Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Lead Spacing - Lead Style - General Purpose -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Maxing Size - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Through Hole Axial 0.098" Dia x 0.150" L (2.50mm x 3.80mm) - Case (Max)	Applications	General Purpose
Package / Case Axial Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.098" Dia x 0.150" L (2.50mm x 3.80mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.098" Dia x 0.150" L (2.50mm x 3.80mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

A330J15C0GL5TAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A330J15C0GL5TAA Payment Methods



















A330J15C0GL5TAA Shipping Methods













If you have any question about A330J15C0GL5TAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com