

A41-130-10

A41-130-10 Information



| A41-130-10 |
|--|
| Signal Transformer |
| Transformers Power Transformers |
| XFRMR LAMINATED 130VA CHAS MOUNT |
| - |
| For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com |
| |



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



A41-130-10 Specifications

| Manufacturer Part NumberA41-130-10Manufacturer ASignal TransformerCategoryTransformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualCenter TapNoPower - MaxI30 VAMounting TypeChasis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WVoltage - Isolation4000VrmsWeightAll Solate, Series | | |
|--|---------------------------------|--------------------------|
| CategoryTansformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCurter TapNoPower - Max130 VAMounting TypeChassis MountSize / DimensionSolder, Quick ConnectSize / Dimension57.0mmHeight - Seated (Max)85.70mmWeight4.1 hs (1.9kg) | Manufacturer Part Number | A41-130-10 |
| InterfactPower TransformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChasis MountSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 hs (1.9kg) | Manufacturer | Signal Transformer |
| Package-SeriesAll-4-One?TypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - MaxI30 VAMounting TypeChasis MountSte/ DimensionSloder, Quick ConnectSte/ Dimension1.40mm Lx 76.20mm WVoltage - Isolation85.70mmWeightMourtmanneSte Joine Second MaxSter Second MaxSter Second MaxSter Second MaxSter Second MaxSter Second MaxSter Joine Second MaxSter Second MaxSecond MaxSter Second MaxS | Category | Transformers |
| SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountStez / Dimension71.40mm L x 76.20mm WStez / Dimension85.70mmVoltage - Isolation41.0by (1.9kg) | | Power Transformers |
| TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualPower - MaxNoPower - MaxSolder, Quick ConnectNounting TypeSolder, Quick ConnectStez / Dimension71.40mm L x 76.20mm WNeight - Seated (Max)\$5.70mmWeight4.1 lbs (1.9kg) | Package | - |
| Yoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmWoltage - Isolation4000VrmsWeight1.1 bs (1.9kg) | Series | All-4-One? |
| Voltage - Secondary (Full Load)Parallel 5V, Series 10VCurrent - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)& 570mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Туре | Laminated Core |
| Current - Output (Max)Parallel 26A, Series 13APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Voltage - Primary | 115V, 230V |
| Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight61.1bs (1.9kg) | Voltage - Secondary (Full Load) | Parallel 5V, Series 10V |
| Secondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight1.1bs (1.9kg) | Current - Output (Max) | Parallel 26A, Series 13A |
| Center TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Primary Winding(s) | Dual |
| Power - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Secondary Winding(s) | Dual |
| Nounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Center Tap | No |
| Termination StyleSolder, Quick ConnectSize / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Power - Max | 130 VA |
| Size / Dimension71.40mm L x 76.20mm WHeight - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Mounting Type | Chassis Mount |
| Height - Seated (Max)85.70mmVoltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Termination Style | Solder, Quick Connect |
| Voltage - Isolation4000VrmsWeight4.1 lbs (1.9kg) | Size / Dimension | 71.40mm L x 76.20mm W |
| Weight 4.1 lbs (1.9kg) | Height - Seated (Max) | 85.70mm |
| | Voltage - Isolation | 4000Vrms |
| Report errors? | Weight | 4.1 lbs (1.9kg) |
| | | Report errors? |

A41-130-10 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

VICE Ser We

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about A41-130-10, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com