

## **A41-130-12A10 Information**

Heisener.com

**Part Number** A41-130-12A10

Manufacturer Pulse Electronics Power

**Category** Transformers

**Power Transformers** 

**Description** XFRMR LAMINATED 130VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# A41-130-12A10 Specifications

Manufacturer Part NumberA41-130-12A10ManufacturerPulse Electronics PowerCategoryTransformersPackage-SeriesInternational High PowerTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 20.6A, Series 10.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.42mm L x 85.85mm WVoltage - Isolation-Weight4.1 lbs (1.9kg)		
CategoryTransformersPackage-SeriesInternational High PowerTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 20.6A, Series 10.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.42mm L x 85.85mm WVoltage - Isolation-Weight4.1 lbs (1.9kg)	Manufacturer Part Number	A41-130-12A10
Package Package International High Power Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V Current - Output (Max) Parallel 20.6A, Series 10.3A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max I 30 VA Mounting Type Chassis Mount Termination Style Size / Dimension T1.42mm L x 85.85mm W Height - Seated (Max) Voltage - Isolation Voltage - Isolation Velight  Power Transformers International High Power International High Po	Manufacturer	Pulse Electronics Power
Package-SeriesInternational High PowerTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 20.6A, Series 10.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.42mm L x 85.85mm WVelight - Seated (Max)73.02mmVoltage - Isolation-Weight4.1 lbs (1.9kg)	Category	Transformers
SeriesInternational High PowerTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 6.3V, Series 12.6VCurrent - Output (Max)Parallel 20.6A, Series 10.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.42mm L x 85.85mm WHeight - Seated (Max)73.02mmVoltage - Isolation-Weight4.1 lbs (1.9kg)		Power Transformers
Type Laminated Core  Voltage - Primary 115V, 230V  Voltage - Secondary (Full Load) Parallel 6.3V, Series 12.6V  Current - Output (Max) Parallel 20.6A, Series 10.3A  Primary Winding(s) Dual  Secondary Winding(s) Dual  Center Tap No  Power - Max 130 VA  Mounting Type Chassis Mount  Termination Style Solder, Quick Connect  Size / Dimension 71.42mm L x 85.85mm W  Height - Seated (Max) 73.02mm  Voltage - Isolation -  Weight 4.1 lbs (1.9kg)	Package	-
Voltage - Primary  Voltage - Secondary (Full Load)  Parallel 6.3V, Series 12.6V  Current - Output (Max)  Parallel 20.6A, Series 10.3A  Primary Winding(s)  Dual  Secondary Winding(s)  Center Tap  No  Power - Max  130 VA  Mounting Type  Chassis Mount  Termination Style  Solder, Quick Connect  Size / Dimension  71.42mm L x 85.85mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Veight  115V, 230V  Parallel 6.3V, Series 12.6V  Parallel 20.6A, Series 10.3A  Parallel 20.6A, Series 10.3A  Parallel 20.6A, Series 10.3A  Parallel 20.6A, Series 10.3A  Parallel 6.3V, Series 12.6V  Parallel 20.6A, Series 10.3A  Primary Winding(s)  Dual  Center Tap  No  130 VA  All 105 (1.9kg)	Series	International High Power
Voltage - Secondary (Full Load)  Current - Output (Max)  Parallel 20.6A, Series 10.3A  Primary Winding(s)  Dual  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  130 VA  Mounting Type  Chassis Mount  Termination Style  Size / Dimension  71.42mm L x 85.85mm W  Height - Seated (Max)  Voltage - Isolation  Voltage - Isolation  Veight  Parallel 6.3V, Series 12.6V  Allel 6.3V, Series 12.6V  Parallel 6.3V, Series 12.6V  Parallel 6.3V, Series 12.6V  Parallel 20.6A, Series 10.3A  Dual  No  4.1 lbs (1.9kg)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 130 VA Mounting Type Chassis Mount Termination Style Size / Dimension Tight - Seated (Max) Voltage - Isolation Veight Parallel 20.6A, Series 10.3A  Dual Canally Chassis Mount Solder Chassis Mount Tanally Chassis Mount Tanally Connect Tanally Chassis Mount Tanally Chassis Mount Tanally Connect Tanally Chassis Mount Tanally Connect Tanally Chassis Mount Tanally Connect Tanally Chassis Mount Tanally Tanally Chassis Mount Tanally	Voltage - Primary	115V, 230V
Primary Winding(s)  Secondary Winding(s)  Dual  Center Tap  No  Power - Max  130 VA  Mounting Type  Chassis Mount  Termination Style  Solder, Quick Connect  Size / Dimension  71.42mm L x 85.85mm W  Height - Seated (Max)  Voltage - Isolation  Veight  Dual  No  130 VA  130 VA  130 VA  130 VA  130 VA  130 VA  142mm L x 85.85mm W  14.1 lbs (1.9kg)	Voltage - Secondary (Full Load)	Parallel 6.3V, Series 12.6V
Secondary Winding(s)DualCenter TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.42mm L x 85.85mm WHeight - Seated (Max)73.02mmVoltage - Isolation-Weight4.1 lbs (1.9kg)	Current - Output (Max)	Parallel 20.6A, Series 10.3A
Center TapNoPower - Max130 VAMounting TypeChassis MountTermination StyleSolder, Quick ConnectSize / Dimension71.42mm L x 85.85mm WHeight - Seated (Max)73.02mmVoltage - Isolation-Weight4.1 lbs (1.9kg)	Primary Winding(s)	Dual
Power - Max  Mounting Type  Chassis Mount  Termination Style  Solder, Quick Connect  Size / Dimension  71.42mm L x 85.85mm W  Height - Seated (Max)  73.02mm  Voltage - Isolation  -  Weight  4.1 lbs (1.9kg)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount  Termination Style Solder, Quick Connect Size / Dimension 71.42mm L x 85.85mm W  Height - Seated (Max) 73.02mm  Voltage - Isolation - Weight 4.1 lbs (1.9kg)	Center Tap	No
Termination Style Solder, Quick Connect Size / Dimension 71.42mm L x 85.85mm W Height - Seated (Max) 73.02mm  Voltage - Isolation - Weight 4.1 lbs (1.9kg)	Power - Max	130 VA
Size / Dimension71.42mm L x 85.85mm WHeight - Seated (Max)73.02mmVoltage - Isolation-Weight4.1 lbs (1.9kg)	Mounting Type	Chassis Mount
Height - Seated (Max)  Voltage - Isolation  Weight  73.02mm  -  4.1 lbs (1.9kg)	Termination Style	Solder, Quick Connect
Voltage - Isolation - 4.1 lbs (1.9kg)	Size / Dimension	71.42mm L x 85.85mm W
Weight 4.1 lbs (1.9kg)	Height - Seated (Max)	73.02mm
	Voltage - Isolation	-
Report errors?	Weight	4.1 lbs (1.9kg)
		Report errors?

#### **A41-130-12A10** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## A41-130-12A10 Payment Methods



















## A41-130-12A10 Shipping Methods













If you have any question about A41-130-12A10, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com