

A41-25-230L

A41-25-230L Information



For Reference Only

Part Number	A41-25-230L	
Manufacturer	Signal Transformer	
Category	Transformers Power Transformers	
Description	XFRMR LAMINATED 25VA CHAS MOUNT	
Package	-	
	For the pricing/inventory/lead time, please contact us	
	Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



A41-25-230L Specifications

Manufacturer Part NumberA41-25-230LManufacturer OSignal TransformerCategoryTransformersPower TransformersPower TransformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualPower - Max25 VAMounting TypeChassis MountTermination StyleSire / DimensionSize / Dimension71.40mm L x 54.40mm WVoltage - Isolation4000VrmsWeight - Seated (Max)Sire / DimensionWeight - Seated (Max)Sire / DimensionMarting - Seated (Max)Sire / DimensionWeight - Seated (Max)Sire / DimensionYotage - IsolationJalles (Sire / Dimension		
CategoryTransformers Power TransformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCurter TapNoPower - Max25 VAMounting TypeChasis MountSize / Dimension71.40mm Lx 54.40mm WSize / DimensionS8.70mmVoltage - IsolationMooVrmsWeightSize / Size / Siz	Manufacturer Part Number	A41-25-230L
Power TransformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountSize / Dimension71.40mm Lx 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Manufacturer	Signal Transformer
Package.SeriesAll-4-One?TypeLaminated CoreVoltage - PrimaryI15V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - MaxSty AMounting TypeChasis MountSter / Dimension14.0mm Lx 54.40mm WSter / DimensionS7.0mmVoltage - IsolationS8.70mmWieghtJ.3 Ils (589.7g)	Category	Transformers
SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm Lx 54.40mm WHeight - Seated (Max)58.70mmWorts4000VrmsWeight1.3 lbs (589.7g)		Power Transformers
TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChasis MountTermination StyleWire LeadsSize / Dimension58.70mmHeight - Seated (Max)58.70mmVoltage - Isolation1.3 lbs (589.7g)	Package	-
Voltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChasis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmWoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Series	All-4-One?
Voltage - Secondary (Full Load)Parallel 115V, Series 230VCurrent - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleVire LeadsSize / Dimension58.70mm L x 54.40mm WHeight - Seated (Max)58.70mmWoltage - Isolation1.3 lbs (589.7g)	Туре	Laminated Core
Current - Output (Max)Parallel 220mA, Series 110mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Voltage - Primary	115V, 230V
Primary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Voltage - Secondary (Full Load)	Parallel 115V, Series 230V
Secondary Winding(s)DualCenter TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Current - Output (Max)	Parallel 220mA, Series 110mA
Center TapNoPower - Max25 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Primary Winding(s)	Dual
Power - Max25 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Secondary Winding(s)	Dual
Mounting TypeChassis MountTermination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Center Tap	No
Termination StyleWire LeadsSize / Dimension71.40mm L x 54.40mm WHeight - Seated (Max)58.70mmVoltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Power - Max	25 VA
Size / Dimension 71.40mm L x 54.40mm W Height - Seated (Max) 58.70mm Voltage - Isolation 4000Vrms Weight 1.3 lbs (589.7g)	Mounting Type	Chassis Mount
Height - Seated (Max) 58.70mm Voltage - Isolation 4000Vrms Weight 1.3 lbs (589.7g)	Termination Style	Wire Leads
Voltage - Isolation4000VrmsWeight1.3 lbs (589.7g)	Size / Dimension	71.40mm L x 54.40mm W
Weight 1.3 lbs (589.7g)	Height - Seated (Max)	58.70mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	1.3 lbs (589.7g)
		Report errors?

A41-25-230L Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about A41-25-230L, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com