

A41-80-24L Information

ha er con

For Reference Only

Part Number A41-80-24L

Manufacturer Signal Transformer

Category Transformers

Power Transformers

Description XFRMR LAMINATED 80VA CHAS MOUNT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









A41-80-24L Specifications

Manufacturer Part NumberA41-80-24LManufacturerSignal TransformerCategoryTransformersPackage-SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 6.6A, Series 3.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension63.50mm L x 64.30mm WHeight - Seated (Max)76.20mmVoltage - Isolation4000VrmsWeight2.8 lbs (1.3kg)		
Category Transformers Power Transformers Package - Series All-4-One? Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 6.6A, Series 3.3A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 80 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) 76.20mm Voltage - Isolation 4000Vrms Weight 2.8 lbs (1.3kg)	Manufacturer Part Number	A41-80-24L
Package Power Transformers All-4-One? Type Laminated Core Voltage - Primary I15V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 6.6A, Series 3.3A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 80 VA Mounting Type Chassis Mount Termination Style Size / Dimension Wire Leads Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Voltage - Isolation Power Transformers All-4-One? Laminated Core Laminated Core Laminated Core All-4-One? Laminated Core All-4-One? Laminated Core Value 12V, Series 24V Parallel 6.6A, Series 3.3A Primary Winding(s) Dual Center Tap No No 60 Chassis Mount Termination Style Voltage - Isolation	Manufacturer	Signal Transformer
Package-SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 6.6A, Series 3.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension63.50mm L x 64.30mm WHeight - Seated (Max)76.20mmVoltage - Isolation4000VrmsWeight2.8 lbs (1.3kg)	Category	Transformers
SeriesAll-4-One?TypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 12V, Series 24VCurrent - Output (Max)Parallel 6.6A, Series 3.3APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension63.50mm L x 64.30mm WHeight - Seated (Max)76.20mmVoltage - Isolation4000VrmsWeight2.8 lbs (1.3kg)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 6.6A, Series 3.3A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 80 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) 76.20mm Voltage - Isolation 4000Vrms Weight	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 12V, Series 24V Current - Output (Max) Parallel 6.6A, Series 3.3A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 80 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension Winding - Seated (Max) Voltage - Isolation Weight Voltage Secondary (Full Load) Parallel 12V, Series 24V Parallel 1	Series	All-4-One?
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 12V, Series 24V Parallel 6.6A, Series 3.3A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 80 VA Mounting Type Chassis Mount Termination Style Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) Voltage - Isolation Weight Parallel 12V, Series 24V Parallel 12V, Series 2.4V Parallel 12V, Series 2.5A Dual Secondary Winding(s) Dual Center Tap No 60 VA Wire Leads 76.20mm Voltage - Isolation Voltage - Isolation Voltage Secondary Winding(s) 2.8 lbs (1.3kg)	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 80 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) Voltage - Isolation Weight Value Parallel 6.6A, Series 3.3A Pual Parallel 6.6A, Series 3.3A Pual Pual Pual Pual Pual Pual Pual Pua	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Dual No Powal No Ro Ro Ro Ro Ro Ro Ro Ro Ro	Voltage - Secondary (Full Load)	Parallel 12V, Series 24V
Secondary Winding(s)DualCenter TapNoPower - Max80 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension63.50mm L x 64.30mm WHeight - Seated (Max)76.20mmVoltage - Isolation4000VrmsWeight2.8 lbs (1.3kg)	Current - Output (Max)	Parallel 6.6A, Series 3.3A
Center Tap Power - Max 80 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) Voltage - Isolation Weight No 80 VA Chassis Mount Vire Leads 63.50mm L x 64.30mm W 76.20mm 4000Vrms 2.8 lbs (1.3kg)	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) 76.20mm Voltage - Isolation 4000Vrms Weight 2.8 lbs (1.3kg)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Wire Leads Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) 76.20mm Voltage - Isolation 4000Vrms Weight 2.8 lbs (1.3kg)	Center Tap	No
Termination Style Size / Dimension 63.50mm L x 64.30mm W Height - Seated (Max) 76.20mm Voltage - Isolation 4000Vrms Weight 2.8 lbs (1.3kg)	Power - Max	80 VA
Size / Dimension63.50mm L x 64.30mm WHeight - Seated (Max)76.20mmVoltage - Isolation4000VrmsWeight2.8 lbs (1.3kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight 76.20mm 4000Vrms 2.8 lbs (1.3kg)	Termination Style	Wire Leads
Voltage - Isolation 4000Vrms Weight 2.8 lbs (1.3kg)	Size / Dimension	63.50mm L x 64.30mm W
Weight 2.8 lbs (1.3kg)	Height - Seated (Max)	76.20mm
	Voltage - Isolation	4000Vrms
Report errors?	Weight	2.8 lbs (1.3kg)
		Report errors?

A41-80-24L Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

A41-80-24L Payment Methods



















A41-80-24L Shipping Methods













If you have any question about A41-80-24L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com